

# ATV630D15N4

variable speed drive ATV630, 15kW/20HP,  
380...480V, IP21/UL type 1

Product availability : Stock - Normally stocked in distribution facility



Price\* : 2,831.00 USD



## Main

|                                  |   |
|----------------------------------|---|
| Range of product                 | Altivar Process ATV600  |
| Product or component type        | Variable speed drive  |
| Product specific application     | Process and utilities   |
| Device short name                | ATV630  |
| Variant                          | Standard version  |
| Product destination              | Synchronous motors<br>Asynchronous motors   |
| EMC filter                       | Integrated with 50 m conforming to EN/IEC 61800-3 category C2<br>Integrated with 150 m conforming to EN/IEC 61800-3 category C3 |
| IP degree of protection          | IP21IEC 61800-5-1<br>IP21IEC 60529  |
| Degree of protection             | UL type 1 UL 508C   |
| Type of cooling                  | Forced convection   |
| Supply frequency                 | 50...60 Hz - 5...5 %  |
| [Us] rated supply voltage        | 380...480 V - 15...10 %   |
| Motor power kW                   | 15 kW (normal duty)<br>11 kW (heavy duty)   |
| Maximum Horse Power Rating       | 20 hp normal duty<br>15 hp heavy duty   |
| Line current                     | 27 A at 380 V (normal duty)<br>23.3 A at 480 V (normal duty)<br>20.6 A at 380 V (heavy duty)<br>18.1 A at 480 V (heavy duty)    |
| Prospective line I <sub>sc</sub> | 50 kA   |
| Apparent power                   | 19.4 kVA at 480 V (normal duty)<br>15 kVA at 480 V (heavy duty)   |
| Continuous output current        | 31.7 A at 4 kHz for normal duty<br>23.5 A at 4 kHz for heavy duty   |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                                    |   |
|------------------------------------|---|
| Maximum transient current          | 34.9 A during 60 s (normal duty)<br>35.3 A during 60 s (heavy duty)   |
| Asynchronous motor control profile | Constant torque standard<br>Variable torque standard<br>Optimized torque mode   |
| Synchronous motor control profile  | Permanent magnet motor<br>Synchronous reluctance motor  |
| Output frequency                   | 0.0001...0.5 kHz  |
| Speed drive output frequency       | 0.1...599 Hz  |
| Nominal switching frequency        | 4 kHz   |
| Switching frequency                | 2...12 kHz adjustable<br>4...12 kHz with derating factor  |
| Safety function                    | STO (safe torque off) SIL 3   |
| Discrete input logic               | 16 preset speeds  |
| Communication port protocol        | Ethernet<br>Modbus serial<br>Modbus TCP   |
| Option card                        | Slot A: communication module, Profibus DP V1<br>Slot A: communication module, Profinet<br>Slot A: communication module, DeviceNet<br>Slot A: communication module, Modbus TCP/EtherNet/IP<br>Slot A: communication module, CANopen daisy chain RJ45<br>Slot A: communication module, CANopen SUB-D 9<br>Slot A: communication module, CANopen screw terminals<br>Slot A/slot B: digital and analog I/O extension module<br>Slot A/slot B: output relay extension module<br>Slot A: communication module, Ethernet IP/Modbus TCP/MD-Link<br>Communication module, BACnet MS/TP<br>Communication module, Ethernet Powerlink |

## Complementary

|                                     |  |
|-------------------------------------|--|
| Mounting mode                       | Wall mount   |
| Output voltage                      | <= power supply voltage  |
| Permissible temporary current boost | 1.1 x I <sub>n</sub> during 60 s (normal duty)<br>1.5 x I <sub>n</sub> during 60 s (heavy duty)  |
| Motor slip compensation             | Can be suppressed<br>Adjustable<br>Automatic whatever the load<br>Not available in permanent magnet motor law  |
| Acceleration and deceleration ramps | Linear adjustable separately from 0.01...9999 s  |
| Braking to standstill               | By DC injection  |
| Protection type                     | Thermal protection motor<br>Safe torque off: motor<br>Motor phase break motor<br>Thermal protection drive<br>Safe torque off: drive<br>Overheating: drive<br>Overcurrent between output phases and earth drive<br>Overload of output voltage: drive<br>Short-circuit protection: drive<br>Motor phase break: drive<br>Overvoltages on the DC bus drive<br>Line supply overvoltage drive<br>Line supply undervoltage drive<br>Line supply phase loss: drive<br>Overspeed: drive<br>Break on the control circuit drive |
| Frequency resolution                | Display unit 0.1 Hz<br>Analog input: 0.012/50 Hz   |
| Electrical connection               | Control: removable screw terminals 0.5...1.5 mm <sup>2</sup> /AWG 20...AWG 16<br>Line side: screw terminal 10...16 mm <sup>2</sup> /AWG 8...AWG 6<br>Motor: screw terminal 10...16 mm <sup>2</sup> /AWG 8...AWG 6  |
| Connector type                      | RJ45 (on the remote graphic terminal) for Ethernet/Modbus TCP<br>RJ45 (on the remote graphic terminal) for Modbus serial   |
| Exchange mode                       | Half duplex, full duplex, autonegotiation Ethernet/Modbus TCP  |

|  |  |
|--|--|
| Number of addresses                        | 1...247 for Modbus serial  |
| Method of access                           | Slave Modbus TCP   |
| Supply                                     | External supply for digital inputs: 24 V DC (19...30 V), <1.25 mA, protection type: overload and short-circuit protection<br>Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC +/- 5 %, <10 mA overload and short-circuit protection<br>Internal supply for digital inputs and STO: 24 V DC (21...27 V), <200 mA, protection type: overload and short-circuit protection  |
| Local signalling                           | 3 LEDs for local diagnostic<br>3 LEDs (dual colour) for embedded communication status<br>4 LEDs (dual colour) for communication module status<br>1 LED (red) for presence of voltage   |
| Width                                      | 8.31 in (211 mm)   |
| Height                                     | 21.50 in (546 mm)  |
| Depth                                      | 9.13 in (232 mm)   |
| Net Weight                                 | 29.98 lb(US) (13.6 kg)   |
| Analogue input number                      | 3  |
| Analogue input type                        | AI1, AI2, AI3 software-configurable voltage: 0...10 V DC, impedance: 30 kOhm, resolution 12 bits<br>AI1, AI2, AI3 software-configurable current: 0...20 mA/4...20 mA, impedance: 250 Ohm, resolution 12 bits   |
| Discrete input number                      | 8  |
| Discrete input type                        | DI1...DI6 programmable, 24 V DC (<= 30 V), impedance: 3.5 kOhm<br>DI5, DI6 programmable as pulse input: 0...30 kHz, 24 V DC (<= 30 V)<br>STOA, STOB safe torque off, 24 V DC (<= 30 V), impedance: > 2.2 kOhm  |
| Input compatibility                        | DI1...DI6: discrete input level 1 PLC conforming to EN/IEC 61131-2<br>DI5, DI6: discrete input level 1 PLC conforming to IEC 65A-68<br>STOA, STOB: discrete input level 1 PLC conforming to EN/IEC 61131-2   |
| Discrete input logic                       | Positive logic (source) (DI1...DI6), < 5 V (state 0), > 11 V (state 1)<br>Negative logic (sink) (DI1...DI6), > 16 V (state 0), < 10 V (state 1)<br>Positive logic (source) (DI5, DI6), < 0.6 V (state 0), > 2.5 V (state 1)<br>Positive logic (source) (STOA, STOB), < 5 V (state 0), > 11 V (state 1)   |
| Analogue output number                     | 2  |
| Analogue output type                       | Software-configurable voltage AO1, AO2: 0...10 V DC impedance 470 Ohm, resolution 10 bits<br>Software-configurable current AO1, AO2: 0...20 mA, resolution 10 bits   |
| Sampling duration                          | 2 ms +/- 0.5 ms (DI1...DI4) - discrete input<br>5 ms +/- 1 ms (DI5, DI6) - discrete input<br>5 ms +/- 0.1 ms (AI1, AI2, AI3) - analog input<br>10 ms +/- 1 ms (AO1) - analog output  |
| Accuracy                                   | +/- 0.6 % AI1, AI2, AI3 for a temperature variation 60 °C analog input<br>+/- 1 % AO1, AO2 for a temperature variation 60 °C analog output   |
| Linearity error                            | AI1, AI2, AI3: +/- 0.15 % of maximum value for analog input<br>AO1, AO2: +/- 0.2 % for analog output   |
| Relay output number                        | 3  |
| Relay output type                          | Configurable relay logic R1: fault relay NO/NC electrical durability 100000 cycles<br>Configurable relay logic R2: sequence relay NO electrical durability 100000 cycles<br>Configurable relay logic R3: sequence relay NO electrical durability 100000 cycles   |
| Refresh time                               | Relay output (R1, R2, R3): 5 ms (+/- 0.5 ms)   |
| Minimum switching current                  | Relay output R1, R2, R3: 5 mA at 24 V DC   |
| Maximum switching current                  | Relay output R1, R2, R3 on resistive load, cos phi = 1: 3 A at 250 V AC<br>Relay output R1, R2, R3 on resistive load, cos phi = 1: 3 A at 30 V DC<br>Relay output R1, R2, R3 on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 250 V AC<br>Relay output R1, R2, R3 on inductive load, cos phi = 0.4 and L/R = 7 ms: 2 A at 30 V DC   |
| Isolation                                  | Between power and control terminals  |
| Variable speed drive application selection | Building - HVAC Compressor centrifugal<br>Food and beverage processing Other application<br>Mining mineral and metal Fan<br>Mining mineral and metal Pump<br>Oil and gas Fan<br>Water and waste water Other application<br>Building - HVAC Screw compressor<br>Food and beverage processing Pump<br>Food and beverage processing Fan<br>Food and beverage processing Atomization<br>Oil and gas Electro submersible pump (ESP)<br>Oil and gas Water injection pump |

Oil and gas Jet fuel pump  
 Oil and gas Compressor for refinery  
 Water and waste water Centrifuge pump  
 Water and waste water Positive displacement pump  
 Water and waste water Electro submersible pump (ESP)  
 Water and waste water Screw pump  
 Water and waste water Lobe compressor  
 Water and waste water Screw compressor  
 Water and waste water Compressor centrifugal  
 Water and waste water Fan  
 Water and waste water Conveyor  
 Water and waste water Mixer

|                        |  |
|------------------------|--|
| Motor power range AC-3 | 15...25 kW 380...440 V 3 phase<br>15...25 kW 480...500 V 3 phase |
|------------------------|--|

## Environment

|                                       |  |
|---------------------------------------|--|
| Insulation resistance                 | > 1 MOhm 500 V DC for 1 minute to earth  |
| Noise level                           | 59.5 dB 86/188/EEC   |
| Power dissipation in W                | Natural convection 59 W 380 V 4 kHz<br>Forced convection 366 W 380 V 4 kHz   |
| Volume of cooling air                 | 56798.01 Gal/hr(US) (215 m3/h)   |
| Operating position                    | Vertical +/- 10 degree   |
| Maximum THDI                          | <48 % from 80...100 % of load conforming to IEC 61000-3-12   |
| Electromagnetic compatibility         | Electrostatic discharge immunity test level 3 IEC 61000-4-2<br>Radiated radio-frequency electromagnetic field immunity test level 3 IEC 61000-4-3<br>Electrical fast transient/burst immunity test level 4 IEC 61000-4-4<br>1.2/50 µs - 8/20 µs surge immunity test level 3 IEC 61000-4-5<br>Conducted radio-frequency immunity test level 3 IEC 61000-4-6 |
| Pollution degree                      | 2 EN/IEC 61800-5-1   |
| Vibration resistance                  | 1.5 mm peak to peak (f= 2...13 Hz) conforming to IEC 60068-2-6<br>1 gn (f= 13...200 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 15 gn 11 ms IEC 60068-2-27   |
| Relative humidity                     | 5...95 % without condensation IEC 60068-2-3  |
| Ambient air temperature for operation | 5...122 °F (-15...50 °C) without derating)<br>122...140 °F (50...60 °C) with derating factor)  |
| Ambient air temperature for storage   | -40...158 °F (-40...70 °C)   |
| Operating altitude                    | <= 3280.84 ft (1000 m) without derating<br>1000...4800 m with current derating 1 % per 100 m   |
| Standards                             | UL 508C<br>EN/IEC 61800-3<br>Environment 1 category C2 EN/IEC 61800-3<br>Environment 2 category C3 EN/IEC 61800-3<br>EN/IEC 61800-5-1<br>IEC 61000-3-12<br>IEC 60721-3<br>IEC 61508<br>IEC 13849-1   |
| Product certifications                | ATEX zone 2/22<br>TÜV<br>ATEX INERIS<br>CSA<br>UL<br>DNV-GL  |
| Marking                               | CE   |

## Ordering and shipping details


|                       |                             |
|-----------------------|-----------------------------|
| Category              | 22206 - ATV630 FRAMES 3 & 4 |
| Discount Schedule     | CP4E                        |
| GTIN                  | 00785901490944              |
| Nbr. of units in pkg. | 1                           |
| Package weight(Lbs)   | 36.59 lb(US) (16.60 kg)     |
| Returnability         | Yes                         |

|                   |    |
|-------------------|----|
| Country of origin | IN |
|-------------------|----|

### Packing Units

|                        |                    |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE                |
| Package 1 Height       | 10.04 in (25.5 cm) |
| Package 1 width        | 13.39 in (34 cm)   |
| Package 1 Length       | 28.94 in (73.5 cm) |


### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |
| Upgradeability             | <a href="#">Upgraded components available</a>    |

Dimensions

Drives with IP21 Top Cover



Front and Left Views




Drives Without IP21 Top Cover

Left and Rear Views

mm  
in.



Clearances




| X1                  | X2                  | X3                 |
|---------------------|---------------------|--------------------|
| ≥ 100 mm (3.94 in.) | ≥ 100 mm (3.94 in.) | ≥ 10 mm (0.39 in.) |




Mounting Types

Mounting Type A: Individual IP21




$a \geq 100 \text{ mm (3.94 in.)}$

Mounting Type B: Side by Side IP20




Mounting Type C: Individual IP20



$a \geq 0$

## Three-Phase Power Supply with Upstream Breaking via Line Contactor


Connection diagrams conforming to standards EN 954-1 category 1 and IEC/EN 61508 capacity SIL1, stopping category 0 in accordance with standard IEC/EN 60204-1



- (1) Line choke if used
- (2) Use relay R1 set to operating state Fault to switch Off the product once an error is detected.
- A1 : Drive
- KM1 : Line Contactor
- Q2, Q3 : Circuit breakers
- S1, S2 : Pushbuttons
- T1 : Transformer for control part


Three-Phase Power Supply with Downstream Breaking via Contactor

Connection diagrams conforming to standards EN 954-1 category 1 and IEC/EN 61508 capacity SIL1, stopping category 0 in accordance with standard IEC/EN 60204-1



- (1) Line choke if used
- (2) Use relay R1 set to operating state Fault to switch Off the product once an error is detected.
- A1 : Drive
- KM1 : Contactor


## Control Block Wiring Diagram



- (1) Safe Torque Off
  - (2) Analog Output
  - (3) Digital Input
  - (4) Reference potentiometer
  - (5) Analog Input
- R1A, R1B, R1C Relay  
R2A, R2C Sequence relay  
R3A, R3C Sequence relay

## Sensor Connection

It is possible to connect either 1 or 3 sensors on terminals AI2 or AI3.




## Sink / Source Switch Configuration


The switch is used to adapt the operation of the logic inputs to the technology of the programmable controller outputs.

- Set the switch to Source (factory setting) if using PLC outputs with PNP transistors.
- Set the switch to Ext if using PLC outputs with NPN transistors.


### Switch Set to SRC (Source) Position Using the Output Power Supply for the Digital Inputs




### Switch Set to SRC (Source) Position and Use of an External Power Supply for the DIs




### Switch Set to SK (Sink) Position Using the Output Power Supply for the Digital Inputs



### Switch Set to EXT Position Using an External Power Supply for the DIs



Derating Curves



- 40 °C (104 °F) - Mounting type A, B and C
  - ⋯ 50 °C (122 °F) - Mounting type A, B and C
  - 60 °C (140 °F) - Mounting type B and C
- In : Nominal Drive Current  
SF : Switching Frequency