



Main

Range of product	Altivar
Product or component type	Communication module

Complementary

Range compatibility	Altivar Process ATV600 Altivar Machine ATV340 except Sercos drives Altivar Machine ATV320 Altivar 32 Altivar Process Modular Altivar Process ATV900
Communication port protocol	Link Layer Discovery Protocol Profinet
Electrical connection	2 connectors RJ45, Ethernet
Transmission rate	100 Mbits
Display type	1 LED for MS (Module Status) 1 LED for NS (Network Status) 1 LED for TX/RX (Transmit/Receive port 1) 1 LED for TX/RX (Transmit/Receive port 2)
Bus profile	PROFIdrive
Product weight	0.3 kg

Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	58 g
Package 1 Height	4.6 cm

Package 1 width	6.5 cm
Package 1 Length	8.9 cm
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Weight	6.877 kg
Package 2 Height	30 cm
Package 2 width	30 cm
Package 2 Length	40 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
PVC free	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov