



Figure similar

MLFB-Ordering data

6SE6440-2UD33-0EA1

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.95
Number of phases	3 AC	Efficiency η	0.96
Line voltage	380 ... 480 V ± 10 %	Ambient conditions	
Line frequency	47 ... 63 Hz	Cooling	Fan
Rated current (LO)	72.00 A	Ambient temperature	
Rated current (HO)	59.00 A	Operation (LO)	-10 ... 40 °C
Output		Operation (HO)	-10 ... 50 °C
Number of phases	3 AC	Transport	-40 ... 70 °C
Rated voltage	480 V	Storage	-40 ... 70 °C
Rated power (LO)	37.00 kW / 50.00 hp		
Rated power (HO)	30.00 kW / 40.00 hp		
Rated current (LO)	75.00 A		
Rated current (HO)	62.00 A		
Pulse frequency	4000 Hz		
Output frequency for V/f control	0 ... 650 Hz		

As a result of legal stipulations, a limit to 550 Hz is in production

Overload capability

Low Overload (LO)

140 % output current for 3 s, followed by 110 % output current for 57 s followed by 100 % output current for 240 s in a 300 s cycle time

High Overload (HO)

150 % output current for 60 s, followed by 100 % output current for 240 s in a 300 s cycle time



Figure similar

Mechanical data	Connections
-----------------	-------------

Degree of protection IP20 / UL open type

Size FSE

Net weight 20.00 kg

Width 275.0 mm

Height 650.0 mm

Depth 245.0 mm

Motor end

Conductor cross-section 35.00 mm²

Inputs / outputs

Standard digital inputs

Number 6

Relay output

Number 3

Analog inputs

Number 2

Analog outputs

Number 2

PTC/ KTY interface

Number 1