

product type designation

SIPLUS S7-1200 CM 1243-5
SIPLUS S7-1200cm 1243-5 -25...+55 °C with conformal coating
based on 6GK7243-5DX30-0XE0 Communication module CM 1243-5, for connecting S7-1200 to PROFIBUS as DP master module



Figure similar

transfer rate	
transfer rate	
• at the 1st interface / acc. to PROFIBUS	9.6 kbit/s ... 12 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	0
number of electrical connections	
• at the 1st interface / acc. to PROFIBUS	1
• for power supply	1
type of electrical connection	
• at the 1st interface / acc. to PROFIBUS	9-pin Sub-D socket (RS485)
• for power supply	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %

relative negative tolerance / at DC / at 24 V	20 %
consumed current <ul style="list-style-type: none"> • from external supply voltage / at DC / at 24 V / typical 	0.1 A
power loss [W]	2.4 W

ambient conditions

ambient temperature <ul style="list-style-type: none"> • for vertical installation / during operation • for horizontally arranged busbars / during operation • during storage • during transport 	-25 ... +45 °C -25 ... +55 °C -40 ... +70 °C -40 ... +70 °C
installation altitude / at height above sea level / maximum	5000 m
ambient condition / relating to ambient temperature - air pressure - installation altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
relative humidity <ul style="list-style-type: none"> • with condensation / acc. to IEC 60068-2-38 / maximum 	100 %; RH including condensation/frost (no commissioning when condensation is present), horizontal installation
chemical resistance / to commercially available cooling lubricants	Yes; incl. airborne diesel and oil droplets
resistance to biologically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 • conformity acc. to EN 60721-3-6 	Yes; Class 3B2 mold and fungal spores (excluding fauna), Class 3B3 on request Yes; Class 6B2 mold, fungal and dry rot spores (excluding fauna)
resistance to chemically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 • conformity acc. to EN 60721-3-6 	Yes; Class 3C4 (RH < 75 %) incl. salt spray in accordance with EN 60068-2-52 (Severity 3). The supplied plug covers must remain in place on the unused interfaces during operation. Yes
resistance to mechanically active substances <ul style="list-style-type: none"> • conformity acc. to EN 60721-3-3 • conformity acc. to EN 60721-3-6 	Yes; Class 3S4 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation. Yes; Class 6S3 incl. sand, dust. The supplied plug covers must remain in place over the unused interfaces during operation.
coating / for equipped printed circuit board / acc. to EN 61086	Yes; Class 2 for high availability
type of coating / protection against pollution according to EN 60664-3	Yes; Protection of the type 1
type of test / of the coating / acc. to MIL-I-46058C	Yes; Coating discoloration during service life possible
product conformity / of the coating / Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal coating, class A

protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-1200 single width
width	30 mm
height	100 mm
depth	75 mm
net weight	0.134 kg
mounting type	
• 35 mm DIN rail mounting	Yes
• S7-300 rail mounting	No
• wall mounting	Yes
product features, product functions, product components / general	
number of units	
• per CPU / maximum	1
performance data / PROFIBUS DP	
service / as DP master	
• DPV1	Yes
number of DP slaves	
• on DP master / usable	16
amount of data	
• of the address area of the inputs / as DP master / total	512 byte
• of the address area of the outputs / as DP master / total	512 byte
• of the address area of the inputs / per DP slave	244 byte
• of the address area of the outputs / per DP slave	244 byte
• of the address area of the diagnostic data / per DP slave	240 byte
service / as DP slave	
• DPV0	No
• DPV1	No
performance data / S7 communication	
number of possible connections / for S7 communication	
• maximum	8; max. 4 connections to other S7 stations
• with PG connections / maximum	1
• with PG/OP connections / maximum	3
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	

- without DP / maximum
- with DP / maximum

8
8

performance data / telecontrol

protocol / is supported

- TCP/IP

No

product functions / management, configuration, engineering

configuration software

- required

STEP 7 Basic/Professional V11 (TIA Portal) or higher

further information / internet-Links

Internet-Link

- to website: Selector TIA Selection Tool
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Image database
- to website: CAx Download Manager
- to website: Industry Online Support

<http://www.siemens.com/snst>

<http://www.siemens.com/simatic-net>

<http://www.siemens.com/industrial-controls/mall>

<http://www.siemens.com/automation/net/catalog>

<http://automation.siemens.com/bilddb>

<http://www.siemens.com/cax>

<http://support.automation.siemens.com>

security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a comprehensive industrial security concept. Siemens products and solutions undergo continuous development with this factor in mind. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Products used from other manufacturers should also be taken into account here. You can find more information on Industrial Security at <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for our product-specific newsletter. You can find more information on this at <http://support.automation.siemens.com>. Version 3.4
14.11.2013- Siemens AG, I IA L CG, Nuremberg

last modified:

10/05/2020