

### product type designation



### CP 243-1

\*\*\*\*\* spare part \*\*\*\*\* communications processor CP 243-1 for connection of SIMATIC S7-22X to Industrial Ethernet; FTP client communication; HTTP server; FTP server; Email client

transfer rate	
transfer rate	
<ul style="list-style-type: none"> <li>at the 1st interface</li> </ul>	10 ... 100 Mbit/s
interfaces	
number of interfaces / acc. to Industrial Ethernet	1
number of electrical connections	
<ul style="list-style-type: none"> <li>at the 1st interface / acc. to Industrial Ethernet</li> </ul>	1
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	1
type of electrical connection	
<ul style="list-style-type: none"> <li>at the 1st interface / acc. to Industrial Ethernet</li> </ul>	RJ45 port
type of electrical connection	
<ul style="list-style-type: none"> <li>for power supply</li> </ul>	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / of the supply voltage	DC
supply voltage / 1 / from backplane bus	5 V
supply voltage / external	24 V
supply voltage / external / at DC / rated value	24 V
relative positive tolerance / at DC / at 24 V	20 %
relative negative tolerance / at DC / at 24 V	15 %
consumed current	
<ul style="list-style-type: none"> <li>from backplane bus / at DC / at 5 V / typical</li> </ul>	0.06 A
<ul style="list-style-type: none"> <li>from external supply voltage / at DC / at 24 V / typical</li> </ul>	0.053 A
<ul style="list-style-type: none"> <li>from external supply voltage / at DC / at 24 V / maximum</li> </ul>	0.06 A
power loss [W]	1.5 W
ambient conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>for vertical installation / during operation</li> </ul>	0 ... 45 °C
<ul style="list-style-type: none"> <li>for horizontally arranged busbars / during operation</li> </ul>	0 ... 55 °C
<ul style="list-style-type: none"> <li>during storage</li> </ul>	-40 ... +70 °C
<ul style="list-style-type: none"> <li>during transport</li> </ul>	-40 ... +70 °C
relative humidity	
<ul style="list-style-type: none"> <li>at 25 °C / without condensation / during operation / maximum</li> </ul>	95 %
protection class IP	IP20
design, dimensions and weights	
module format	Compact module S7-200 double width
width	71.2 mm

height	80 mm
depth	62 mm
net weight	0.15 kg
<b>product features, product functions, product components / general</b>	
number of units	1
• per CPU / maximum	1
• note	-
<b>performance data / S7 communication</b>	
number of possible connections / for S7 communication	8
• maximum	8
• with PG connections / maximum	1
• with PG/OP connections / maximum	8
<b>performance data / IT functions</b>	
number of possible connections	1
• as client / by means of FTP / maximum	1
number of possible connections	4
• as server / by means of HTTP / maximum	4
• as email client / maximum	1
number of emails with 1024 characters / of email client / maximum	32
number of access authorizations / of access protection	8
storage capacity / of the user memory	8 Mibyte
• as flash memory file system	8 Mibyte
number of possible write cycles / of the flash memory cells	100000
<b>performance data / telecontrol</b>	
protocol / is supported	Yes
• TCP/IP	Yes
<b>product functions / management, configuration, engineering</b>	
product function / MIB support	No
protocol / is supported	No
• SNMP v1	No
configuration software	STEP 7-Micro/WIN Version V4.0 SP8 or higher
• required	STEP 7-Micro/WIN Version V4.0 SP8 or higher
<b>product functions / diagnostics</b>	
product function / web-based diagnostics	Yes
<b>product functions / switch</b>	
product feature / switch	No
<b>standards, specifications, approvals / hazardous environments</b>	
certificate of suitability / CCC / for hazardous zone according to GB standard	Yes
<b>further information / internet-Links</b>	
Internet-Link	
• to web page: selection aid TIA Selection Tool	<a href="http://www.siemens.com/tia-selection-tool">http://www.siemens.com/tia-selection-tool</a>
• to website: Industrial communication	<a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>
• to website: Industry Mall	<a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>
• to website: Information and Download Center	<a href="http://www.siemens.com/industry/infocenter">http://www.siemens.com/industry/infocenter</a>
• to website: Image database	<a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>
• to website: CAx-Download-Manager	<a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>
• to website: Industry Online Support	<a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>
<b>security information</b>	
security information	Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <a href="http://www.siemens.com/industrialsecurity">http://www.siemens.com/industrialsecurity</a> . To stay informed about

---

product updates as they occur, sign up for a product-specific newsletter.  
For more information, visit <http://support.automation.siemens.com>.  
(V3.4)

**last modified:**

8/3/2021 