

SIPLUS S7-300 CPU 315F-2DP -25...+60°C with conformal coating based on 6ES7315-6FF04-0AB0 . Fail-safe module with MPI Integr. power supply 24 V DC, Work memory 384 KB, 40 mm width, 2nd interface DP master/ slave Micro Memory Card required



Figure similar

General information	
Product function	
• Isochronous mode	Yes
Engineering with	
• Programming package	STEP 7 V5.5 + SP1 or higher or STEP 7 V5.2 + SP1 or higher with HSP 218 + Distributed Safety
Supply voltage	
Rated value (DC)	
• 24 V DC	Yes
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	2 A min.
Mains buffering	
• Mains/voltage failure stored energy time	5 ms
• Repeat rate, min.	1 s
Input current	

Current consumption (rated value)	850 mA
Current consumption (in no-load operation), typ.	150 mA
Inrush current, typ.	3.5 A
I^2t	1 A ² ·s

Power loss

Power loss, typ.	4.5 W
------------------	-------

Memory

Work memory

• integrated	384 kbyte
• expandable	No
• Size of retentive memory for retentive data blocks	128 kbyte

Load memory

• Plug-in (MMC)	Yes
• Plug-in (MMC), max.	8 Mbyte
• Data management on MMC (after last programming), min.	10 y

Backup

• present	Yes; Guaranteed by MMC (maintenance-free)
• without battery	Yes; Program and data

CPU processing times

for bit operations, typ.	0.05 µs
for word operations, typ.	0.09 µs
for fixed point arithmetic, typ.	0.12 µs
for floating point arithmetic, typ.	0.45 µs

CPU-blocks

Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
--------------------------	---

DB

• Number, max.	1 024; Number range: 1 to 16000
• Size, max.	64 kbyte

FB

• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	64 kbyte

FC

• Number, max.	1 024; Number range: 0 to 7999
• Size, max.	64 kbyte

OB

• Description	see instruction list
• Size, max.	64 kbyte
• Number of free cycle OBs	1; OB 1

• Number of time alarm OBs	1; OB 10
• Number of delay alarm OBs	2; OB 20, 21
• Number of cyclic interrupt OBs	4; OB 32, 33, 34, 35
• Number of process alarm OBs	1; OB 40
• Number of DPV1 alarm OBs	3; OB 55, 56, 57
• Number of isochronous mode OBs	1; OB 61
• Number of startup OBs	1; OB 100
• Number of asynchronous error OBs	5; OB 80, 82, 85, 86, 87
• Number of synchronous error OBs	2; OB 121, 122

Nesting depth

• per priority class	16
• additional within an error OB	4

Counters, timers and their retentivity

S7 counter

• Number	256
----------	-----

Retentivity

— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	Z 0 to Z 7

Counting range

— lower limit	0
— upper limit	999

IEC counter

• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)

S7 times

• Number	256
----------	-----

Retentivity

— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	No retentivity

Time range

— lower limit	10 ms
— upper limit	9 990 s

IEC timer

• present	Yes
• Type	SFB
• Number	Unlimited (limited only by RAM capacity)

Data areas and their retentivity

retentive data area in total	all, 128 KB max.
Flag	
• Number, max.	2 048 byte
• Retentivity available	Yes; MB 0 to MB 2 047
• Retentivity preset	MB 0 to MB 15
• Number of clock memories	8; 1 memory byte
Data blocks	
• Retentivity adjustable	Yes; via non-retain property on DB
• Retentivity preset	Yes
Local data	
• per priority class, max.	32 kbyte; Max. 2 KB per block
Address area	
I/O address area	
• Inputs	2 048 byte
• Outputs	2 048 byte
of which distributed	
— Inputs	2 048 byte
— Outputs	2 048 byte
Process image	
• Inputs	2 048 byte
• Outputs	2 048 byte
• Inputs, adjustable	2 048 byte
• Outputs, adjustable	2 048 byte
• Inputs, default	384 byte
• Outputs, default	384 byte
Subprocess images	
• Number of subprocess images, max.	1
Digital channels	
• Inputs	16 384
— of which central	1 024
• Outputs	16 384
— of which central	1 024
Analog channels	
• Inputs	1 024
— of which central	256
• Outputs	1 024
— of which central	256
Hardware configuration	
Number of expansion units, max.	3
Number of DP masters	

<ul style="list-style-type: none"> • integrated 	1
<ul style="list-style-type: none"> • via CP 	4
Number of operable FMs and CPs (recommended)	
<ul style="list-style-type: none"> • FM 	8
<ul style="list-style-type: none"> • CP, PtP 	8
<ul style="list-style-type: none"> • CP, LAN 	10
Rack	
<ul style="list-style-type: none"> • Racks, max. 	4
<ul style="list-style-type: none"> • Modules per rack, max. 	8
Time of day	
Clock	
<ul style="list-style-type: none"> • Hardware clock (real-time) 	Yes
<ul style="list-style-type: none"> • retentive and synchronizable 	Yes
<ul style="list-style-type: none"> • Backup time 	6 wk; At 40 °C ambient temperature
<ul style="list-style-type: none"> • Deviation per day, max. 	10 s; Typ.: 2 s
<ul style="list-style-type: none"> • Behavior of the clock following POWER-ON 	Clock continues running after POWER OFF
<ul style="list-style-type: none"> • Behavior of the clock following expiry of backup period 	Clock continues to run with the time at which the power failure occurred
Operating hours counter	
<ul style="list-style-type: none"> • Number 	1
<ul style="list-style-type: none"> • Number/Number range 	0
<ul style="list-style-type: none"> • Range of values 	0 to 2 ³¹ hours (when using SFC 101)
<ul style="list-style-type: none"> • Granularity 	1 h
<ul style="list-style-type: none"> • retentive 	Yes; Must be restarted at each restart
Clock synchronization	
<ul style="list-style-type: none"> • supported 	Yes
<ul style="list-style-type: none"> • to MPI, master 	Yes
<ul style="list-style-type: none"> • to MPI, slave 	Yes
<ul style="list-style-type: none"> • to DP, master 	Yes; With DP slave only slave clock
<ul style="list-style-type: none"> • to DP, slave 	Yes
<ul style="list-style-type: none"> • in AS, master 	Yes
<ul style="list-style-type: none"> • in AS, slave 	No
Digital inputs	
Number of digital inputs	0
Digital outputs	
Number of digital outputs	0
Analog inputs	
Number of analog inputs	0
Analog outputs	
Number of analog outputs	0

Interfaces	
Number of industrial Ethernet interfaces	0
Number of PROFINET interfaces	0
Number of RS 485 interfaces	2
Number of RS 422 interfaces	0

1. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	No
Power supply to interface (15 to 30 V DC), max.	200 mA

Protocols

• MPI	Yes
• PROFIBUS DP master	No
• PROFIBUS DP slave	No
• Point-to-point connection	No

MPI

• Transmission rate, max.	187.5 kbit/s
---------------------------	--------------

Services

— PG/OP communication	Yes
— Routing	Yes
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No
— S7 communication, as server	Yes

2. Interface

Interface type	Integrated RS 485 interface
Physics	RS 485
Isolated	Yes
Power supply to interface (15 to 30 V DC), max.	200 mA

Protocols

• MPI	No
• PROFIBUS DP master	Yes
• PROFIBUS DP slave	Yes
• Point-to-point connection	No

PROFIBUS DP master

• Transmission rate, max.	12 Mbit/s
• Number of DP slaves, max.	124; Per station

Services

— PG/OP communication	Yes
— Routing	Yes

— Global data communication	No
— S7 basic communication	Yes; I blocks only
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No
— S7 communication, as server	Yes
— Equidistance	Yes
— Isochronous mode	Yes; OB 61
— SYNC/FREEZE	Yes
— Activation/deactivation of DP slaves	Yes
— Number of DP slaves that can be simultaneously activated/deactivated, max.	8
— DPV1	Yes
Address area	
— Inputs, max.	2 048 byte
— Outputs, max.	2 048 byte
User data per DP slave	
— Inputs, max.	244 byte
— Outputs, max.	244 byte
PROFIBUS DP slave	
• GSD file	The latest GSD file is available at: http://www.siemens.com/profibus-gsd
• Transmission rate, max.	12 Mbit/s
• automatic baud rate search	Yes; only with passive interface
• Address area, max.	32
• User data per address area, max.	32 byte
Services	
— PG/OP communication	Yes
— Routing	Yes; Only with active interface
— Global data communication	No
— S7 basic communication	No
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No
— S7 communication, as server	Yes
— Direct data exchange (slave-to-slave communication)	Yes
— DPV1	No
Transfer memory	
— Inputs	244 byte
— Outputs	244 byte
Isochronous mode	
Isochronous operation (application synchronized up to terminal)	Yes

Communication functions	
PG/OP communication	Yes
Data record routing	Yes
Global data communication	
<ul style="list-style-type: none"> supported 	Yes
<ul style="list-style-type: none"> Number of GD loops, max. 	8
<ul style="list-style-type: none"> Number of GD packets, max. 	8
<ul style="list-style-type: none"> Number of GD packets, transmitter, max. 	8
<ul style="list-style-type: none"> Number of GD packets, receiver, max. 	8
<ul style="list-style-type: none"> Size of GD packets, max. 	22 byte
<ul style="list-style-type: none"> Size of GD packet (of which consistent), max. 	22 byte
S7 basic communication	
<ul style="list-style-type: none"> supported 	Yes
<ul style="list-style-type: none"> User data per job, max. 	76 byte
<ul style="list-style-type: none"> User data per job (of which consistent), max. 	76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
<ul style="list-style-type: none"> supported 	Yes
<ul style="list-style-type: none"> as server 	Yes
<ul style="list-style-type: none"> as client 	Yes; Via CP and loadable FB
<ul style="list-style-type: none"> User data per job, max. 	180 byte; With PUT/GET
<ul style="list-style-type: none"> User data per job (of which consistent), max. 	240 byte; as server
S5 compatible communication	
<ul style="list-style-type: none"> supported 	Yes; via CP and loadable FC
Number of connections	
<ul style="list-style-type: none"> overall 	16
<ul style="list-style-type: none"> usable for PG communication 	15
<ul style="list-style-type: none"> <ul style="list-style-type: none"> reserved for PG communication 	1
<ul style="list-style-type: none"> <ul style="list-style-type: none"> adjustable for PG communication, min. 	1
<ul style="list-style-type: none"> <ul style="list-style-type: none"> adjustable for PG communication, max. 	15
<ul style="list-style-type: none"> usable for OP communication 	15
<ul style="list-style-type: none"> <ul style="list-style-type: none"> reserved for OP communication 	1
<ul style="list-style-type: none"> <ul style="list-style-type: none"> adjustable for OP communication, min. 	1
<ul style="list-style-type: none"> <ul style="list-style-type: none"> adjustable for OP communication, max. 	15
<ul style="list-style-type: none"> usable for S7 basic communication 	12
<ul style="list-style-type: none"> <ul style="list-style-type: none"> reserved for S7 basic communication 	0
<ul style="list-style-type: none"> <ul style="list-style-type: none"> adjustable for S7 basic communication, min. 	0
<ul style="list-style-type: none"> <ul style="list-style-type: none"> adjustable for S7 basic communication, max. 	12
S7 message functions	

Number of login stations for message functions, max.	16; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	300

Test commissioning functions

Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4

Status/control

• Status/control variable	Yes
• Variables	Inputs, outputs, memory bits, DB, times, counters
• Number of variables, max.	30
— of which status variables, max.	30
— of which control variables, max.	14

Forcing

• Forcing	Yes
• Forcing, variables	Inputs, outputs
• Number of variables, max.	10

Diagnostic buffer

• present	Yes
• Number of entries, max.	500
— adjustable	No
— of which powerfail-proof	100; Only the last 100 entries are retained
• Number of entries readable in RUN, max.	
— adjustable	Yes; From 10 to 499
— preset	10

Service data

• can be read out	Yes
-------------------	-----

Standards, approvals, certificates

CE mark	Yes
UL approval	Yes; File E239877
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes

Use in hazardous areas

• ATEX	Yes
--------	-----

Railway application

• EN 50155	No
------------	----

Ambient conditions

Ambient temperature during operation	
• min.	-25 °C

• max.	60 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Configuration	
Configuration software	
• STEP 7	Yes; V5.2 SP1 or higher with HW update
Programming	
• Command set	see instruction list
• Nesting levels	8
• System functions (SFC)	see instruction list

• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— CFC	Yes
— GRAPH	Yes
— HiGraph®	Yes
Know-how protection	
• User program protection/password protection	Yes
• Block encryption	Yes; With S7 block Privacy
Dimensions	
Width	40 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	290 g
last modified:	10/09/2020