

SIMATIC S7-300, Digital input SM 321, isolated, 16 DI; 24 V DC, 1x 20-pole, process interrupt, diagnostics, suitable for isochronous mode



Figure similar

Supply voltage	
Load voltage L+	
• Rated value (DC)	24 V
• permissible range, lower limit (DC)	20.4 V
• permissible range, upper limit (DC)	28.8 V
• Reverse polarity protection	Yes
Input current	
from load voltage L+ (without load), max.	90 mA
from backplane bus 5 V DC, max.	130 mA
Encoder supply	
Number of outputs	2
Type of output voltage	L+ (-2.5 V)
Short-circuit protection	Yes; Electronic
additional (redundant) feed	Yes
Output current	
• Rated value	120 mA

- permissible range, lower limit 0 mA
- permissible range, upper limit 150 mA

Power loss

Power loss, typ.	4 W
------------------	-----

Digital inputs

Number of digital inputs	16
--------------------------	----

Input characteristic curve in accordance with IEC 61131, type 2	Yes
---	-----

Number of simultaneously controllable inputs

horizontal installation

— up to 40 °C, max.	16
---------------------	----

— up to 60 °C, max.	16
---------------------	----

vertical installation

— up to 40 °C, max.	16
---------------------	----

Input voltage

• Type of input voltage	DC
-------------------------	----

• Rated value (DC)	24 V
--------------------	------

• for signal "0"	-30 to +5 V
------------------	-------------

• for signal "1"	13 to 30V
------------------	-----------

Input current

• for signal "1", typ.	7 mA
------------------------	------

Input delay (for rated value of input voltage)

for standard inputs

— parameterizable	Yes; 0.1 / 0.5 / 3 / 15 / 20 ms
-------------------	---------------------------------

Encoder connection

• Fixed current limitation for wire-break monitoring, min.	10 kΩ
--	-------

• Fixed current limitation for wire-break monitoring, max.	18 kΩ
--	-------

Cable length

• shielded, max.	1 000 m
------------------	---------

• unshielded, max.	600 m
--------------------	-------

Encoder

Connectable encoders

• 2-wire sensor	Yes
-----------------	-----

— permissible quiescent current (2-wire sensor), max.	2 mA
---	------

Interrupts/diagnostics/status information

Alarms	Yes
--------	-----

Diagnostics function	Yes; Parameterizable
----------------------	----------------------

Alarms	
--------	--

• Diagnostic alarm	Yes; Parameterizable
• Hardware interrupt	Yes; Parameterizable
Diagnoses	
• Diagnostic information readable	Yes
• Wire-break	Yes; to I < 1 mA
Diagnostics indication LED	
• Group error SF (red)	Yes
• Status indicator digital input (green)	Yes
• Encoder supply Vs (green)	Yes
Potential separation	
Potential separation digital inputs	
• between the channels	No
• between the channels, in groups of	16
• between the channels and backplane bus	Yes; Optocoupler
Isolation	
Isolation tested with	500 V DC
Connection method	
required front connector	20-pin
Dimensions	
Width	40 mm
Height	125 mm
Depth	120 mm
Weights	
Weight, approx.	200 g
last modified:	10/13/2020