

CONNECTING CABLE S7 UNSHIELDED 1.0M
 Connecting cable unshielded for SIMATIC S7-300/1500 between front connector module and Connection module 16x0.14mm² with IDC connectors, L = 1.0 m



Figure similar

Target system	SIMATIC S7-300 / 1500
Suitability for use	Digital I/O modules
Product type designation	Fully modular connection
Product designation	Pre-assembled round cable

Operating data	
Operating voltage / at DC	
<ul style="list-style-type: none"> Rated value 	24 V
<ul style="list-style-type: none"> maximum 	60 V
Ambient temperature	
<ul style="list-style-type: none"> during operation 	0 ... 60 °C
<ul style="list-style-type: none"> during storage 	-30 ... +70 °C

General data	
Suitability for interaction	
<ul style="list-style-type: none"> Input card PLC 	Yes
<ul style="list-style-type: none"> PLC output card 	Yes
Suitability for use	
<ul style="list-style-type: none"> digital signal transmission 	Yes

- analog signal transmission

No

Product properties, functions, components / general

Number of channels	8
Design of cable	Round cable
Wire length	1 m
Number of poles	16
Number of conductors / of connecting cable	16
Conductor cross section / Rated value	0.14 mm ²
Color / of cable sheath	Black
Outer diameter / of cable sheath	6.5 mm
Material / of the connecting cable sheath	PVC
Connector type	IDC connector
Type of electrical connection / on enclosure	Connector strip
Number of poles / at the 1st interface	16; cable side front connector module
Type of electrical connection / in the field	Connector strip
Number of poles / at the 2nd interface	16; on the connection module
Certificate of suitability / cULus approval	No
Equipment marking / acc. to DIN EN 81346-2	W
Net weight	0.125 kg
last modified:	03/11/2020