

32K TERM.L BL. TP1 W. LED PUSH-IN TERM.
 Connection module TP1 32 channels a. 4x2 terminals f. Potential
 supply Type: Push-in terminal with LED, VPE=1 unit 50 pole IDC
 connector for cable



Figure similar

| | |
|--------------------------|--------------------------|
| Target system | SIMATIC S7-1500 |
| Suitability for use | Digital I/O modules |
| Product type designation | Fully modular connection |
| Product designation | Connection module |

| Operating data | |
|---|----------------|
| Operating voltage | |
| • at DC / Rated value | 24 V |
| • rated value | 50 V |
| • at DC / maximum | 24 V |
| Current / rated value | 1 A |
| Continuous current / at DC / per signal cable / maximum | 1 A |
| Total current / maximum | 2 A |
| Operating temperature | 0 ... 60 °C |
| Ambient temperature | |
| • during operation | 0 ... 60 °C |
| • during storage | -40 ... +70 °C |

| | |
|--|--|
| Number of terminal levels | 1 |
| Number of terminal points / per terminal level | 1 |
| Number of terminals | 40; 32 x I/O; 4 x L+, 4 x M |
| Type of connecting terminal | Push-In |
| Type of electrical connection / for actuators and sensors | Push-In |
| Position / of the terminal | Top |
| Design of LED initiator/actuator terminal | Push-In |
| Width of screwdriver blade | 3.5 mm |
| Design of terminal / Terminal levels internally linked | No |
| Product component | |
| • PE connection | No |
| • Shield connection | No |
| • Disconnecter | No |
| • required / connection plate | No |
| Product feature / Infeed function | Yes |
| Product feature / cross-connectable | No |
| Number of cables / per connection | 2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule. |
| Type of connectable conductor cross-sections / solid | No |
| Connectable conductor cross-section | |
| • for flexible conductor / with core end processing | 0.2 ... 2.5 mm ² ; End sleeve according to DIN 46228/1 or DIN 46228/4 with plastic collar |
| • stranded | 0.2 ... 2.5 mm ² |
| • finely stranded / without core end processing | 0.2 ... 2.5 mm ² |
| • finely stranded / with core end processing | 0.2 ... 2.5 mm ² |
| Number of poles / at the 1st interface | 50; the IDC connector for the connection cable |
| Type of electrical connection / for connecting cable | Plug-in connection |
| number of the plug contacts / of the electrical connection | 1 |
| Wire length / maximum | 30 m; between front connector module and Connection module |

General data

| | |
|--|--------------------------------|
| Mounting type | DIN rail 35 mm, DIN rail 15 mm |
| Installation or assembly note | any |
| Mounting position | any |
| Degree of pollution | 2 |
| Overvoltage category | 2 |
| Combustibility class acc. to UL 94 | V1 |
| Insulation material | other |
| Design tested acc. to type of protection / EEx e | No |
| Certificate of suitability / cULus approval | Yes |
| Reference code / acc. to DIN EN 81346-2 | X |
| Color | |

| | |
|---|---------|
| • of the enclosure | grey |
| • of the light source | other |
| Length | 76 mm |
| Height / of the enclosure | 76 mm |
| Width / of the enclosure | 100 mm |
| Depth / of the enclosure | 60 mm |
| Height / with lowest-profile installation | 60 mm |
| Net weight | 0.21 kg |