

SIPLUS S7-400 PS 407 10 A -25...+70°C with conformal coating based on 6ES7407-0KA02-0AA0 . 10A, Wide "range, ""UC 120/230V; 5 V DC/10" "A""



Figure similar

| Supply voltage                                      |       |
|---|-------|
| Rated value (DC)                                    |       |
| • 120 V DC  | Yes   |
| • 230 V DC  | Yes   |
| Rated value (AC)                                    |       |
| • 120 V AC  | Yes   |
| • 230 V AC  | Yes   |
| Line frequency                                      |       |
| • Rated value 50 Hz                                 | Yes   |
| • Rated value 60 Hz                                 | Yes   |
| • permissible range, lower limit                    | 47 Hz |
| • permissible range, upper limit                    | 63 Hz |
| Mains buffering                                     |       |
| • Mains/voltage failure stored energy time          | 20 ms |
| • Mains buffering according to NAMUR recommendation | Yes   |
| Input current                                       |       |

|                         |                                       |
|-------------------------|---------------------------------------|
| Rated value at 110 V DC | 1 A; at 120 V DC                      |
| Rated value at 230 V DC | 0.5 A                                 |
| Rated value at 120 V AC | 0.9 A                                 |
| Rated value at 230 V AC | 0.5 A                                 |
| Inrush current, max.    | 63 A; Full width at half maximum 1 ms |
| Leakage current, max.   | 3.5 mA                                |

| Output voltage         |     |
|------------------------|-----|
| Type of output voltage | DC  |
| Rated value (DC)       |     |
| • 5 V DC               | Yes |
| • 24 V DC              | Yes |

| Output current                    |                             |
|-----------------------------------|-----------------------------|
| for backplane bus (5 V DC), max.  | 10 A; no base load required |
| for backplane bus (24 V DC), max. | 1 A; idling-proof           |
| Short-circuit protection          | Yes                         |

| Power                    |      |
|--------------------------|------|
| Active power input, typ. | 95 W |

| Power loss       |      |
|------------------|------|
| Power loss, typ. | 20 W |

| Battery                     |  |
|-----------------------------|--|
| Backup battery              |  |
| • Backup battery (optional) | Yes; 0 °C to +60 °C: 2x lithium AA; 3.6 V/2.3 Ah // -25 °C to +70 °C and/or 100 % RH: 2x external battery box 6AG1971-0AA00-7AA0 and 2x MONO cell design D |

| Hardware configuration |   |
|------------------------|---|
| Slots                  |   |
| • required slots       | 2 |

| Potential separation |     |
|----------------------|-----|
| primary/secondary    | Yes |

| Isolation            |    |
|----------------------|----|
| Overvoltage category | II |

| EMC   |     |
|---|-----|
| Compliance with line harmonic distortion limits                                 |     |
| • Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3 | Yes |

| Degree and class of protection |                              |
|--------------------------------|------------------------------|
| Equipment protection class     | I, with protective conductor |

| Ambient conditions                   |  |
|--------------------------------------|--|
| Ambient temperature during operation |  |

|   |   |
|---|---|
| • min.  | -25 °C; using the external battery box SIPLUS 6AG1971-0AA00-7AA0 for buffer mode  |
| • max.  | 70 °C; using the external battery box SIPLUS 6AG1971-0AA00-7AA0 for buffer mode   |
| <b>Altitude during operation relating to sea level</b>  |   |
| • Installation altitude above sea level, max.   | 2 000 m   |
| • Ambient air temperature-barometric pressure-altitude  | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m)  |
| <b>Relative humidity</b>  |   |
| • With condensation, tested in accordance with IEC 60068-2-38, max.   | 100 %; RH incl. condensation/frost (no commissioning if there is condensation). In buffer mode, use battery box SIPLUS 6AG1971-0AA00-7AA0 for high humidity                         |
| <b>Resistance</b>   |   |
| <b>Use in stationary industrial systems</b>   |   |
| — to biologically active substances according to EN 60721-3-3   | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request  |
| — to chemically active substances according to EN 60721-3-3   | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-3   | Yes; Class 3S4 incl. sand, dust, *  |
| <b>Use on ships/at sea</b>  |   |
| — to biologically active substances according to EN 60721-3-6   | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request   |
| — to chemically active substances according to EN 60721-3-6   | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *  |
| — to mechanically active substances according to EN 60721-3-6   | Yes; Class 6S3 incl. sand, dust; *  |
| <b>Usage in industrial process technology</b>   |   |
| — Against chemically active substances acc. to EN 60654-4   | Yes; Class 3 (excluding trichlorethylene)   |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04                | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| <b>Remark</b>   |   |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation!  |
| <b>Conformal coating</b>  |   |
| • Coatings for printed circuit board assemblies acc. to EN 61086  | Yes; Class 2 for high reliability   |
| • Protection against fouling acc. to EN 60664-3   | Yes; Type 1 protection  |
| • Military testing according to MIL-I-46058C, Amendment 7   | Yes; Discoloration of coating possible during service life  |

- Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A

Yes; Conformal coating, Class A

#### Connection method

Design of electrical connection

3x 1.5 mm<sup>2</sup>, solid or stranded wire with end sleeve, external diameter 3 mm to 9 mm

#### Dimensions

Width

50 mm

Height

290 mm

Depth

217 mm

#### Weights

Weight, approx.

1 200 g

**last modified:**

10/09/2020