

SIMATIC S7-400, digital input SM 421, isolated 16 DI; 24 V DC with 0.05 ms input delay alarm, diagnostics



Supply voltage

Load voltage L+

| | |
|---------------------------------------|--------|
| • Rated value (DC) | 24 V |
| • permissible range, lower limit (DC) | 20.4 V |
| • permissible range, upper limit (DC) | 28.8 V |

Input current

| | |
|---------------------------------|--------|
| from supply voltage L+, max. | 120 mA |
| from backplane bus 5 V DC, max. | 130 mA |

Encoder supply

| | |
|-----------------------------|-----------------|
| Number of outputs | 2 |
| Type of output voltage | L+ (-2.5 V) |
| Short-circuit protection | Yes; Electronic |
| additional (redundant) feed | Yes; possible |

Output current

| | |
|----------------------------------|--------|
| • Rated value | 120 mA |
| • permissible range, lower limit | 0 mA |
| • permissible range, upper limit | 150 mA |

| | |
|--|---|
| Power loss | |
| Power loss, typ. | 5 W |
| Digital inputs | |
| Number of digital inputs | 16 |
| Number of simultaneously controllable inputs | |
| • Number of simultaneously controllable inputs | 16 |
| Input voltage | |
| • Type of input voltage | DC |
| • Rated value (DC) | 24 V |
| • for signal "0" | -30 V DC to +5 V DC |
| • for signal "1" | 11 V DC to 30 V DC |
| Input current | |
| • for signal "0", min. | 6 mA; < 6 mA |
| • for signal "1", typ. | 6 mA; 6 to 8 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | Yes |
| — at "0" to "1", min. | 3 µs; 0.05 / 0.1 / 0.5 / 3 ms |
| Encoder connection | |
| • Fixed current limitation for wire-break monitoring, min. | 10 kΩ |
| • Fixed current limitation for wire-break monitoring, max. | 18 kΩ |
| Cable length | |
| • shielded, max. | 1 000 m; 1 000 m: 3 ms, 70 m: 0.5 ms, 30 m: 0.1 ms, 30 m: 0.05 ms |
| • unshielded, max. | 600 m; 600 m: 3 ms; 50 m: 0.5 ms; 20 m: 0.1 ms; 20 m: 0.05 ms |
| Encoder | |
| Connectable encoders | |
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 3 mA |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes; Parameterizable |
| Alarms | |
| • Diagnostic alarm | Yes; Parameterizable |
| • Hardware interrupt | Yes; Parameterizable |
| Diagnoses | |
| • Diagnostic information readable | Yes |
| • Monitoring the supply voltage | Yes |
| • Wire-break | Yes; I < 1 mA |

Diagnostics indication LED

| | |
|--|----------------|
| • Rated load voltage PWR (green) | Yes; Per group |
| • internal fault INTF (red) | Yes |
| • external fault EXTF (red) | Yes |
| • Status indicator digital input (green) | Yes |
| • Channel fault indicator F (red) | No |

Potential separation

Potential separation digital inputs

| | |
|--|-----|
| • between the channels | Yes |
| • between the channels, in groups of | 8 |
| • between the channels and backplane bus | Yes |

Isolation

| | |
|-----------------------|----------|
| Isolation tested with | 500 V DC |
|-----------------------|----------|

Dimensions

| | |
|--------|--------|
| Width | 25 mm |
| Height | 290 mm |
| Depth | 210 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 600 g |
|-----------------|-------|

last modified: 10/16/2020