

SIMATIC S7-400, analog input SM 431, 8 AI, resolution 16 bit, resistor/PT100/Ni100 isolated, diagnostics alarm, 20 ms conversion time



Figure similar

Input current	
from backplane bus 5 V DC, max.	650 mA
Power loss	
Power loss, typ.	3.3 W
Analog inputs	
Number of analog inputs	8
• For resistance measurement	8
permissible input voltage for voltage input (destruction limit), max.	35 V; 35 V continuous, 75 V for max. 1 s (mark to space ratio 1:20)
Constant measurement current for resistance-type transmitter, typ.	1 mA
Input ranges	
• Voltage	No
• Current	No
• Thermocouple	No
• Resistance thermometer	Yes
• Resistance	Yes

Input ranges (rated values), resistance thermometer	
<ul style="list-style-type: none"> • Ni 100 <ul style="list-style-type: none"> — Input resistance (Ni 100) • Ni 1000 <ul style="list-style-type: none"> — Input resistance (Ni 1000) • Pt 100 <ul style="list-style-type: none"> — Input resistance (Pt 100) • Pt 1000 <ul style="list-style-type: none"> — Input resistance (Pt 1000) • Pt 200 <ul style="list-style-type: none"> — Input resistance (Pt 200) • Pt 500 <ul style="list-style-type: none"> — Input resistance (Pt 500) 	<p>Yes</p> <p>> 10 000 ohms</p> <p>Yes; Different characteristics selectable: Europe/U.S.</p> <p>> 10 000 ohms</p> <p>Yes</p> <p>> 10 000 ohms</p> <p>Yes</p> <p>> 10 000 ohms</p> <p>Yes</p> <p>> 10 000 ohms</p> <p>Yes</p> <p>> 10 000 ohms</p>
Characteristic linearization	
<ul style="list-style-type: none"> • parameterizable <ul style="list-style-type: none"> — for resistance thermometer 	<p>Yes</p> <p>Pt100, Pt200, Pt500, Pt1000, Ni100, Ni1000; different characteristics selectable (Europe/U.S.)</p>
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	<p>200 m; 50 m with thermocouples and input ranges ± 80 mV</p>
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. • Integration time, parameterizable • Basic conversion time (ms) • Integration time (ms) • Interference voltage suppression for interference frequency f_1 in Hz 	<p>16 bit</p> <p>Yes</p> <p>8 / 23 / 25 ms</p> <p>20 ms at 50 Hz (entire module incl. wire break)</p> <p>none/ 60 / 50 Hz</p>
Encoder	
Connection of signal encoders	
<ul style="list-style-type: none"> • for resistance measurement with three-wire connection • for resistance measurement with four-wire connection 	<p>Yes</p> <p>Yes</p>
Errors/accuracies	
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> • Resistance thermometer, relative to input range, (+/-) 	<p>± 1 °C</p>
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> • Resistance thermometer, relative to input range, (+/-) 	<p>$\pm 0,2$ °C</p>

Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
• Diagnostic alarm	Yes; Parameterizable
• Limit value alarm	Yes
• Hardware interrupt	Yes; Parameterizable
Diagnoses	
• Diagnostic information readable	Yes; possible
Potential separation	
Potential separation analog inputs	
• Potential separation analog inputs	Yes; internal/external
• between the channels	No
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	500 V DC
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	650 g
last modified:	10/13/2020