

SIMATIC S7-400, coupling module CP 440-1 for point-to-point connections, 1 channel incl. configuration package on CD



Figure similar

Supply voltage	
Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes
Input current	
from backplane bus 5 V DC, max.	360 mA
Power loss	
Power loss, typ.	1.7 W
Memory	
Memory requirements per interface in memory card of S7-CPU	1 to 5 Kbytes for parameters
Interfaces	
Number of interfaces	1
Point-to-point connection	
Integrated protocol driver	
— 3964 (R)	Yes

— ASCII	Yes
<b>Transmission rate, RS 422/485</b>	
— with 3964 (R) protocol, max.	115.2 kbit/s
— with ASCII protocol, max.	115.2 kbit/s
<b>Ambient conditions</b>	
<b>Ambient temperature during operation</b>	
• min.	0 °C
• max.	60 °C
<b>Ambient temperature during storage/transportation</b>	
• min.	0 °C
• max.	70 °C
<b>Relative humidity</b>	
• Operation, max.	95 %; no condensation
<b>Configuration</b>	
<b>Configuration software</b>	
• STEP 7	Yes; own parameter assignment forms
<b>Dimensions</b>	
Width	25 mm
Height	290 mm
Depth	210 mm
<b>Weights</b>	
Weight, approx.	600 g
<b>last modified:</b>	10/13/2020