Data sheet

SIMATIC S7, MODBUS Master V3.1 single license for 1 installation R-SW, SW and DOCU on CD, HW dongle, Class A, 3 languages (de, de, fr, en fr), executable in STEP 7 V4.02 or higher, reference hardware: CP 341 and CP 441-2



Figure similar

Standards, approvals, certificates	
developed in accordance with IEC 61131	Yes
Operating systems	
Runs under operating system	
• Windows 9x	No
 Windows ME 	No
• Windows NT 4.0	No
• Windows 2000	No
Windows XP	Yes
• Windows 7	Yes
Software	
Software class	A
Runtime software	
Target system	SIMATIC CP 341/CP 441-2
Adjustable parameters	
Response monitoring time	100 ms to 25.5 s in 100-ms grid

Factor for the character delay time
 Modem operation (ignore filler characters)
 RS 485 operation for 2-wire connection
 Preassignment of receive circuit on application

Communication data

of the X.27 interface module

CRC polynomial
 Receive mailbox
 Modbus protocol
 X16 + x15 + x2 + 1
 Specified on BRCV
 with RTU format

• implemented function codes 01, 02, 03, 04, 05, 06, 07, 08, 11, 12, 15, 16

Broadcast Message possib

• Transmission rate 300 bit/s to 76 800 bit/s; (TTY to 19 200 bit/s)

V.24 control and signal cables

• Character delay time 3.5 characters or multiples

Authorization/licenses

• Single license (EL) Yes

Documentation

Languages

GermanEnglishFrenchYes

last modified: 10/13/2020



PNAP