

# Product datasheet

Specifications



## C60 - circuit breaker - C60N - 2P - 10A - C curve

24336

! Discontinued on: 23 January 2021

! End-of-service on: 24 January 2021

! Discontinued

24336 has not been replaced. Please contact your customer care centre for more information.

### Main

Range of product	C60
Range	Multi 9
Product name	C60
Product or component type	Miniature circuit-breaker
Device short name	C60N
Device application	Distribution
Poles description	2P
Number of protected poles	2
Neutral position	Left
[In] rated current	10 A at 30 °C
Network type	AC
Trip unit technology	Thermal-magnetic
Curve code	C
Breaking capacity	20 kA Icu at 130 V AC 50/60 Hz conforming to EN/IEC 60947-2 10 kA Icu at 230...240 V AC 50/60 Hz conforming to EN/IEC 60947-2 3 kA Icu at 400...415 V AC 50/60 Hz conforming to EN/IEC 60947-2 6000 A Icn at 230/400 V AC 50/60 Hz conforming to EN 60898 15 kA Icu at 60 V DC 1P conforming to EN/IEC 60947-2
Suitability for isolation	Yes conforming to IEC 60947-2

### Complementary

Network frequency	50/60 Hz
[Ue] rated operational voltage	230...240 V AC 50/60 Hz 400...415 V AC 50/60 Hz 130 V AC 50/60 Hz 230/400 V AC 50/60 Hz
Magnetic tripping limit	5...10 x In
[Ics] rated service breaking capacity	15 kA conforming to EN/IEC 60947-2 - 130 V AC 50/60 Hz 7.5 kA conforming to EN/IEC 60947-2 - 230...240 V AC 50/60 Hz 6000 A conforming to EN 60898 - 230/400 V AC 50/60 Hz 2.25 kA conforming to EN/IEC 60947-2 - 400...415 V AC 50/60 Hz
Limitation class	3 conforming to EN/IEC 60947-2
Contact position indicator	Yes

Control type	Toggle
Local signalling	ON/OFF indication
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
9 mm pitches	4
Height	81 mm
Width	36 mm
Depth	73 mm
Net weight	0.24 kg
Mechanical durability	20000 cycles
Connections - terminals	Tunnel type terminals16 mm <sup>2</sup> flexible Tunnel type terminals25 mm <sup>2</sup> rigid
Earth-leakage protection	Separate block

## Environment

Standards	EN/IEC 60947-2 IEC 60898
Tropicalisation	2 conforming to IEC 60068-1
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-25...60 °C
Ambient air temperature for storage	-40...70 °C

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	206 g
Package 1 Height	3.6 cm
Package 1 width	7.5 cm
Package 1 Length	8.5 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	18 months
----------	-----------