

DATA SHEFT

CI855

System 800xA hardware selector



The MasterBus 300 (MB300) communication protocol used in communication between controllers, operator stations in installations based on Advant OCS with Master software is also implemented in the System 800xA controller AC 800M. MB 300 communication is realized in AC 800M by communication interface CI855, which is connected to the CEX-Bus through a baseplate.

The baseplate, TP853, houses RJ45 connectors for two Ethernet ports, for network redundancy and provides a simple DIN-rail mounting.

A key benefit with the CI855 interface is the possibility of having peer-to-peer communication between new plant sections with System 800xA using the AC 800M controller and existing sections with MB 300-based controllers like Advant Controller 410, Advant Controller 450 and MasterPiece 200/1.

Features and benefits

- MB 300 network redundancy
- Clock synchronization
- DataSet communication
- Hot swap
- Per to peer communication

| General info | | |
|----------------------------------|---------------------------|--|
| Article number | 3BSE018106R1 | |
| Protocol | ABB's MasterBus 300 | |
| Master or slave | Master | |
| Transmission speed | 10 Mbit/s, 200 Datasets/s | |
| Line redundancy | No | |
| Module redundancy | No | |
| Hot Swap | Yes | |
| Used together with HI Controller | Ves | |

| Detailed data | | |
|-----------------------|----------------------|--|
| Max units on CEX bus | 12 | |
| Connector | RJ-45 female (8-pin) | |
| 24 V consumption typ. | typ 150 mA | |

| Environment and certification | | |
|-------------------------------|--------------------------------------|--|
| Temperature, Operating | 55 °C | |
| Protection class | IP20 according to EN60529, IEC 529 | |
| CE- marking | Yes | |
| Marine certificates | BV, DNV-GL, LR | |
| RoHS compliance | DIRECTIVE/2011/65/EU (EN 50581:2012) | |
| WEEE compliance | DIRECTIVE/2012/19/EU | |

| Dimensions | | |
|-------------------------|--------------------|--|
| Height | 185 mm (7.3 in.) | |
| Width | 59 mm (2.3 in.) | |
| Depth | 127.5 mm (5.0 in.) | |
| Weight (including base) | 700 g (1.5 lbs) | |





solutions.abb/800xA solutions.abb/controlsystems

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2022 ABB All rights reserved

