


DO840

System 800xA hardware selector



This module has 16 digital outputs. The maximum continuous output current per channel is 0.5 A. The outputs are current limited and protected against over temperature. The outputs are divided into two groups with eight output channels and one voltage supervision input in each group. Each output channel consists of a current limited and over temperature protected high side driver, EMC protection components, inductive load suppression, output state indication LED and optical isolation barrier.

Features and benefits

- 16 channels for 24 V d.c. current sourcing outputs
- 2 isolated groups of 8 channels with process voltage supervision
- Advanced on-board diagnostics
- Output status indicators
- OSP sets outputs to predetermined state upon error detection
- Redundant or single applications
- Current limited and over-temperature protection

| General info | |
|----------------------|-------------------------------------|
| Article number | 3BSE020838R1 |
| Type | Digital Output |
| Signal specification | 24 V d.c. (19.2 - 32 V d.c.), 0.5 A |
| Number of channels | 16 |
| Signal type | Current sourcing, current limiting |
| HART | No |
| SOE | No |
| Redundancy | Yes |
| High integrity | No |
| Intrinsic safety | No |
| Mechanics | S800 |

| Detailed data | |
|-------------------------------------|--|
| Isolation | Groupwise isolated from ground |
| Current limiting | Short circuit proof current limited output |
| Maximum field cable length | 600 meters (656 yards) |
| Rated insulation voltage | 50 V |
| Dielectric test voltage | 500 V a.c. |
| Power dissipation | Typ. 4.3 W |
| Current consumption +5 V Modulebus | 130 mA |
| Current consumption +24 V Modulebus | 0 |
| Current consumption +24 V external | 200 mA |

| Diagnostics | |
|----------------------------------|---|
| Front LED's | F(ault), R(un), W(arning), O(SP), Channel 1-16 Status |
| Supervision | Process power 1 per group |
| Status indication of supervision | Module Error, Module Warning, Channel error |

| Environment and certification | |
|---------------------------------|---|
| CE mark | Yes |
| Electrical safety | IEC 61131-2, UL 61010-1, UL 61010-2-201 |
| Hazardous Location | C1 Div 2 cULus, C1 Zone 2 cULus, ATEX Zone 2 |
| Marine certification | DNV-GL |
| Protection rating | IP20 according to IEC 60529 |
| Corrosive atmosphere ISA-S71.04 | G3 |
| Climatic operating conditions | 0 to +55 °C (Storage -40 to +70 °C), RH=5 to 95 % no condensation, IEC/EN 61131-2 |
| Pollution degree | Degree 2, IEC 60664-1 |
| Mechanical operating conditions | IEC/EN 61131-2 |
| EMC | EN 61000-6-4, EN 61000-6-2 |
| Overvoltage categories | IEC/EN 60664-1, EN 50178 |
| Equipment class | Class I according to IEC 61140; (earth protected) |
| Max ambient temperature | 55 °C (131 °F), for vertical mounting in compact MTU 40 °C (104 °F) |
| RoHS compliance | DIRECTIVE/2011/65/EN (EN 50581:2012) |
| WEEE compliance | DIRECTIVE/2012/19/EU |

| Compability | |
|--------------|--|
| Use with MTU | TU810, TU812, TU814, TU830, TU833, TU842, TU843, TU852 |
| Keying code | CE |

| Dimensions | |
|------------|--|
| Width | 45 mm (1.77") |
| Depth | 102 mm (4.01"), 111 mm (4.37") including connector |
| Height | 119 mm (4.7") |
| Weight | 0.15 kg (0.33 lbs.) |

Related products



TU810V1



TU812V1



TU814V1



TU830V1



TU833



TU842



TU843



TU852

solutions.abb/800xA
solutions.abb/controlsystems

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2022 ABB All rights reserved