

# AIS810

## System 800xA hardware selector



Select I/O is an Ethernet networked, single channel granular I/O system for the ABB Ability™ System 800xA automation platform. Select I/O helps decouple project tasks, minimizes the impact of late changes and supports standardization of I/O cabinetry ensuring automation projects are delivered on-time and under budget. A Signal Conditioning Module (SCM) performs the necessary signal conditioning and powering of the connected field device for one I/O channel.

The AIS810 is an Analog Input Signal Conditioning Module (16 bit) supporting 2/4-wire devices and HART communications.

### Features and benefits

- Analog input for 2-wire or external powered 4-wire field devices
- Signal range: 4...20 mA and 0...20 mA
- Can be used in hazardous areas
- Transmitter power current limited to 30 mA
- 16 bit A/D converter resolution
- Channel to channel galvanic isolation
- Hardware filter, rise time 1ms
- Software filter configurable through parameters
- Protected against wrong wiring
- Configurable software filter
- Diagnostics:
  - Loop supervision (open circuit and short circuit)
  - Hardware error supervision
  - Communication supervision
  - Device malfunction low, underrange, overrange and device malfunction high detection
  - Internal power supervision
- Support of HART field devices (up to HART application layer revision7):
  - HART Pass-Through
  - Cyclic read of up to two HART Device Variables
  - HART Device Validation
- Single loop granularity - each SCM handles a single channel
- Supports hot swap
- Mechanical locking slider which turns off field device power and/or output before removal
- Field disconnect function which can galvanically separate the field loop wiring from the SCM during commissioning and maintenance
- All SCMs have electronic current limitation
- Mechanical keying to prevent insertion of wrong module type after commissioning
- 24V DC powered through Modulebus
- Configurable through parameters
- LED indicators on the SCM indicate the operational state of the module.

General info	
Article number	3BSE078762R1
Type	Analog Input
Signal specification	4-20 mA 0-20 mA (no HART)
HART	Yes
Detailed HART information	HART v7, HART pass-through and HART variables to the application
SOE	N/A
Redundancy	Yes
Hot swap	Yes
High integrity	No
Intrinsic safety	No
Mechanics	Select I/O

Detailed data	
Supported field devices	2-wire and 4-wire devices (external power required for 4-wire devices)
Isolation	Galvanic isolation to system and between each channel (including field power). Routine tested at factory with 3060 VDC.
Field power	Current limited to 30 mA
Accuracy	0.1 %
Resolution	16-bit A/D converter
Diagnostics	- Loop supervision (short circuit and open circuit) - Under range and over range Device Malfunction - Low and Device Malfunction High - Internal hardware supervision - Communication supervision - Internal power supervision
Calibration	Factory calibration
Power dissipation	0.62 W at 20 mA
Installation in Hazardous Locations	ATEX – II 3G Ex nA/eC IIC T4 Gc Class I, Zone 2, IIC T4 Class I, Div 2, Groups A, B, C, D T4 Non-incendive or non-arcing field wiring acc. to Division model
IS barrier	No
Field Input Robustness	±35 V between all terminals
Input impedance	250 ohm

Environment and certification	
Temperature, Operating	-40°C (-40°F) to +70°C (158°F)
Temperature, Storage	-40°C (-40°F) to +85°C (185°F)
Pollution degree	Degree 2, IEC 60664-1
Relative humidity	5 to 95 % no condensation
Altitude	-1000 to 3000 m, (-100 ... 2000 m for Zone 2/Class I Div 2)
Mechanical operating conditions	IEC 61131-2
EMC	IEC/EN 61000-6-4, IEC/EN 61000-6-2
Overvoltage categories	Category II, IEC 60664-1
Protection class	IP20 according to IEC 60529
CE-marking	Yes
Electrical Safety	IEC/EN 61010-1, IEC 61010-2-201, UL 61010-2-201, CSA C22.2 No. 61010-2-201
Hazardous Area	EN 60079-0, EN60079-7, EN60079-15, UL 12.12.01 / CSA C22.2 No. 213-17
Marine certification	DNV-GL, ABS
Corrosive atmosphere	G3 (ISA-S71.04)
RoHS compliance	DIRECTIVE/2011/65/EU (EN 50581:2012)
WEEE compliance	DIRECTIVE/2012/19/EU

---

**Dimensions**

---

Width	77.9 mm (3.06 in.)
Depth	105 mm (4.13 in.)
Height	9.8 mm (0.39 in.)
Weight (including base)	73 g (0.16 lbs)

---

[solutions.abb/800xA](https://solutions.abb/800xA)  
[solutions.abb/controlsystems](https://solutions.abb/controlsystems)

800xA is a registered or pending trademark of ABB. All rights to other trademarks reside with their respective owners.

We reserve the right to make technical changes to the products or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not assume any responsibility for any errors or incomplete information in this document.

We reserve all rights to this document and the items and images it contains. The reproduction, disclosure to third parties or the use of the content of this document – including parts thereof – are prohibited without ABB's prior written permission.

Copyright© 2022 ABB All rights reserved