

# ATV71HD45N4

variable speed drive ATV71 - 45kW-60HP - 480V  
- EMC filter-graphic terminal

Product availability : Stock - Normally stocked in distribution facility



Price\* : 7,753.30 USD



⚠ To be discontinued

## Commercial status

Discontinued on: 31 December 2020

End-of-service soon on: 01 January 2028

### Main

|                                    |   |
|------------------------------------|---|
| Range of product                   | Altivar 71  |
| Product or component type          | Variable speed drive  |
| Product specific application       | Complex, high-power machines  |
| Component name                     | ATV71   |
| Motor power kW                     | 45 kW, 3 phase 380...480 V  |
| Maximum Horse Power Rating         | 60 hp, 3 phase 380...480 V  |
| Maximum motor cable length         | 328.08 ft (100 m) shielded cable<br>656.17 ft (200 m) unshielded cable  |
| Power supply voltage               | 380...480 V - 15...10 %   |
| Phase                              | 3 phase   |
| Line current                       | 104 A 380 V 3 phase 45 kW / 60 hp<br>85 A 480 V 3 phase 45 kW / 60 hp   |
| EMC filter                         | Integrated  |
| Assembly style                     | With heat sink  |
| Apparent power                     | 68.5 kVA 380 V 3 phase 45 kW / 60 hp  |
| Prospective line I <sub>sc</sub>   | 22 kA 3 phase   |
| Nominal output current             | 77 A 2.5 kHz 460 V 3 phase 45 kW / 60 hp<br>94 A 2.5 kHz 380 V 3 phase 45 kW / 60 hp  |
| Maximum transient current          | 141 A 60 s 3 phase 45 kW / 60 hp<br>155 A 2 s 3 phase 45 kW / 60 hp   |
| Output frequency                   | 0.1...500 Hz  |
| Nominal switching frequency        | 2.5 kHz   |
| Switching frequency                | 1...16 kHz adjustable<br>2.5...16 kHz with derating factor  |
| Asynchronous motor control profile | Flux vector control (FVC) with sensor (current vector)<br>Voltage/frequency ratio (2 or 5 points)<br>ENA (Energy adaptation) system for unbalanced loads<br>Sensorless flux vector control (SFVC) (voltage or current vector) |

\* Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                      |                     |
|----------------------|---------------------|
| Type of polarization | No impedance Modbus |
|----------------------|---------------------|

## Complementary

|  |  |
|--|--|
| Product destination                        | Synchronous motors<br>Asynchronous motors  |
| Power supply voltage limits                | 323...528 V  |
| Power supply frequency                     | 50...60 Hz - 5...5 %   |
| Power supply frequency limits              | 47.5...63 Hz   |
| Speed range                                | 1...100 asynchronous motor in open-loop mode, without speed feedback<br>1...1000 asynchronous motor in closed-loop mode with encoder feedback<br>1...50 synchronous motor in open-loop mode, without speed feedback  |
| Speed accuracy                             | +/- 0.01 % of nominal speed in closed-loop mode with encoder feedback 0.2 Tn to Tn<br>+/- 10 % of nominal slip without speed feedback 0.2 Tn to Tn   |
| Torque accuracy                            | +/- 15 % in open-loop mode, without speed feedback<br>+/- 5 % in closed-loop mode with encoder feedback  |
| Transient overtorque                       | 170 % +/- 10 % 60 s every 10 minutes<br>220 % +/- 10 % 2 s   |
| Braking torque                             | <= 150 % with braking or hoist resistor<br>30 % without braking resistor   |
| Synchronous motor control profile          | Vector control without speed feedback  |
| Regulation loop                            | Adjustable PI regulator  |
| Motor slip compensation                    | Automatic whatever the load<br>Not available in voltage/frequency ratio (2 or 5 points)<br>Suppressable<br>Adjustable  |
| Diagnostic                                 | Drive voltage 1 LED red)   |
| Output voltage                             | <= power supply voltage  |
| Insulation                                 | Electrical between power and control   |
| Type of cable for mounting in an enclosure | With a NEMA Type1 kit 3 UL 508 cable 104 °F (40 °C), copper 75 °C / PVC<br>With an IP21 or an IP31 kit 3 IEC cable 104 °F (40 °C), copper 70 °C / PVC<br>Without mounting kit 1 IEC cable 113 °F (45 °C), copper 70 °C / PVC<br>Without mounting kit 1 IEC cable 113 °F (45 °C), copper 90 °C / XLPE/EPR |
| Electrical connection                      | Terminal 2.5 mm <sup>2</sup> , AWG 14 AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)<br>Terminal 150 mm <sup>2</sup> L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)  |
| Tightening torque                          | 5.31 lbf.in (0.6 N.m) AI1-/AI1+, AI2, AO1, R1A, R1B, R1C, R2A, R2B, LI1...LI6, PWR)<br>362.88 lbf.in (41 N.m), 360 lb.in L1/R, L2/S, L3/T, U/T1, V/T2, W/T3, PC/-, PO, PA/+, PA, PB)   |
| Supply                                     | Internal supply for reference potentiometer (1 to 10 kOhm) 10.5 V DC +/- 5 %, <10 mA overload and short-circuit protection<br>Internal supply 24 V DC 21...27 V), <200 mA overload and short-circuit protection  |
| Analogue input number                      | 2  |
| Analogue input type                        | AI1-/AI1+ bipolar differential voltage +/- 10 V DC 24 V max 11 bits + sign<br>AI2 software-configurable current 0...20 mA 242 Ohm 11 bits<br>AI2 software-configurable voltage 0...10 V DC 24 V max 30000 Ohm 11 bits  |
| Input sampling time                        | 2 ms +/- 0.5 ms AI1-/AI1+) - analog<br>2 ms +/- 0.5 ms AI2) - analog<br>2 ms +/- 0.5 ms LI1...LI5) - discrete<br>2 ms +/- 0.5 ms LI6)if configured as logic input - discrete   |
| Response time                              | <= 100 ms in STO (Safe Torque Off)<br>AO1 2 ms +/- 0.5 ms analog<br>R1A, R1B, R1C 7 ms +/- 0.5 ms discrete<br>R2A, R2B 7 ms +/- 0.5 ms discrete  |
| Absolute accuracy precision                | +/- 0.6 % AI1-/AI1+) for a temperature variation 60 °C<br>+/- 0.6 % AI2) for a temperature variation 60 °C<br>+/- 1 % AO1) for a temperature variation 60 °C   |
| Linearity error                            | +/- 0.15 % of maximum value AI1-/AI1+, AI2)<br>+/- 0.2 % AO1)  |
| Analogue output number                     | 1  |
| Analogue output type                       | AO1 software-configurable logic output 10 V 20 mA<br>AO1 software-configurable current 0...20 mA 500 Ohm 10 bits<br>AO1 software-configurable voltage 0...10 V DC 470 Ohm 10 bits  |
| Discrete output number                     | 2  |
| Discrete output type                       | Configurable relay logic R1A, R1B, R1C) NO/NC - 100000 cycles  |

|                                     |   |
|-------------------------------------|---|
|                                     | Configurable relay logic R2A, R2B) NO - 100000 cycles   |
| Minimum switching current           | 3 mA 24 V DC configurable relay logic   |
| Maximum switching current           | R1, R2 2 A 250 V AC inductive, cos phi = 0.4<br>R1, R2 2 A 30 V DC inductive, cos phi = 0.4<br>R1, R2 5 A 250 V AC resistive, cos phi = 1<br>R1, R2 5 A 30 V DC resistive, cos phi = 1  |
| Discrete input number               | 7   |
| Discrete input type                 | LI1...LI5 programmable 24 V DC level 1 PLC 3500 Ohm<br>LI6 switch-configurable 24 V DC level 1 PLC 3500 Ohm<br>LI6 switch-configurable PTC probe 0...6 1500 Ohm<br>PWR safety input 24 V DC 1500 Ohm ISO 13849-1 level d  |
| Discrete input logic                | Negative logic (sink) LI1...LI5), > 16 V, < 10 V<br>Positive logic (source) LI1...LI5), < 5 V, > 11 V<br>Negative logic (sink) LI6)if configured as logic input, > 16 V, < 10 V<br>Positive logic (source) LI6)if configured as logic input, < 5 V, > 11 V  |
| Acceleration and deceleration ramps | S, U or customized<br>Linear adjustable separately from 0.01 to 9000 s<br>Automatic adaptation of ramp if braking capacity exceeded, by using resistor  |
| Braking to standstill               | By DC injection   |
| Protection type                     | Against exceeding limit speed drive<br>Against input phase loss drive<br>Break on the control circuit drive<br>Input phase breaks drive<br>Line supply overvoltage drive<br>Line supply undervoltage drive<br>Overcurrent between output phases and earth drive<br>Overheating protection drive<br>Overvoltages on the DC bus drive<br>Short-circuit between motor phases drive<br>Thermal protection drive<br>Motor phase break motor<br>Power removal motor<br>Thermal protection motor |
| Insulation resistance               | > 1 mOhm 500 V DC for 1 minute to earth   |
| Frequency resolution                | Analog input 0.024/50 Hz<br>Display unit 0.1 Hz   |
| Communication port protocol         | Modbus<br>CANopen   |
| Connector type                      | 1 RJ45 on front face)Modbus<br>1 RJ45 on terminal)Modbus<br>Male SUB-D 9 on RJ45CANopen   |
| Physical interface                  | 2-wire RS 485 Modbus  |
| Transmission frame                  | RTU Modbus  |
| Transmission rate                   | 4800 bps, 9600 bps, 19200 bps, 38.4 Kbps Modbus on terminal<br>9600 bps, 19200 bps Modbus on front face<br>20 kbps, 50 kbps, 125 kbps, 250 kbps, 500 kbps, 1 Mbps CANopen   |
| Data format                         | 8 bits, 1 stop, even parity Modbus on front face<br>8 bits, odd even or no configurable parity Modbus on terminal   |
| Number of addresses                 | 1...127 CANopen<br>1...247 Modbus   |
| Method of access                    | Slave CANopen   |
| Marking                             | CE  |
| Operating position                  | Vertical +/- 10 degree  |
| Height                              | 24.80 in (630 mm)   |
| Depth                               | 11.42 in (290 mm)   |
| Width                               | 12.60 in (320 mm)   |
| Net Weight                          | 97.00 lb(US) (44 kg)  |
| Functionality                       | Full  |
| Specific application                | Other applications  |
| Option card                         | Communication card CC-Link<br>Controller inside programmable card<br>Communication card DeviceNet<br>Communication card Ethernet/IP<br>Communication card Fipio   |

I/O extension card  
 Communication card Interbus-S  
 Interface card for encoder  
 Communication card Modbus Plus  
 Communication card Modbus TCP  
 Communication card Modbus/Uni-Telway  
 Overhead crane card  
 Communication card Profibus DP  
 Communication card Profibus DP V1

## Environment

|                                       |   |
|---------------------------------------|---|
| Noise level                           | 63.7 dB 86/188/EEC  |
| Dielectric strength                   | 3535 V DC between earth and power terminals<br>5092 V DC between control and power terminals  |
| Electromagnetic compatibility         | 1.2/50 $\mu$ s - 8/20 $\mu$ s surge immunity test level 3 IEC 61000-4-5<br>Conducted radio-frequency immunity test level 3 IEC 61000-4-6<br>Electrical fast transient/burst immunity test level 4 IEC 61000-4-4<br>Electrostatic discharge immunity test level 3 IEC 61000-4-2<br>Radiated radio-frequency electromagnetic field immunity test level 3 IEC 61000-4-3<br>Voltage dips and interruptions immunity test IEC 61000-4-11 |
| Standards                             | UL Type 1<br>EN 61800-3 environments 1 category C3<br>IEC 60721-3-3 class 3S2<br>EN 61800-3 environments 2 category C3<br>IEC 60721-3-3 class 3C1<br>EN 55011 class A group 2<br>EN/IEC 61800-3<br>EN/IEC 61800-5-1   |
| Product certifications                | NOM 117<br>CSA<br>UL<br>C-tick<br>GOST  |
| Pollution degree                      | 2 EN/IEC 61800-5-1<br>3 UL 840  |
| IP degree of protection               | IP20  |
| Vibration resistance                  | 1 gn 13...200 Hz)EN/IEC 60068-2-6<br>1.5 mm peak to peak 3...13 Hz)EN/IEC 60068-2-6   |
| Shock resistance                      | 15 gn 11 ms EN/IEC 60068-2-27   |
| Relative humidity                     | 5...95 % without condensation IEC 60068-2-3<br>5...95 % without dripping water IEC 60068-2-3  |
| Ambient air temperature for operation | 14...122 °F (-10...50 °C) without derating)   |
| Ambient air temperature for storage   | -13...158 °F (-25...70 °C)  |
| Operating altitude                    | <= 3280.84 ft (1000 m) without derating<br>3280.84...9842.52 ft (1000...3000 m) with current derating 1 % per 100 m   |

## Ordering and shipping details

|                       |                                      |
|-----------------------|--------------------------------------|
| Category              | 22132 - ATV71 - 60 THRU 150HP DRIVES |
| Discount Schedule     | CP4C                                 |
| GTIN                  | 00785901966500                       |
| Nbr. of units in pkg. | 1                                    |
| Package weight(Lbs)   | 1 lb(US) (0.45 kg)                   |
| Returnability         | No                                   |
| Country of origin     | IN                                   |

## Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Package 1 Height       | 14.17 in (36 cm) |
| Package 1 width        | 19.69 in (50 cm) |
| Package 1 Length       | 30.31 in (77 cm) |
| Unit Type of Package 2 | P06              |

|                              |                        |
|------------------------------|------------------------|
| Number of Units in Package 2 | 1                      |
| Package 2 Weight             | 93.70 lb(US) (42.5 kg) |
| Package 2 Height             | 30.31 in (77 cm)       |
| Package 2 width              | 31.50 in (80 cm)       |
| Package 2 Length             | 23.62 in (60 cm)       |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

### ATV71HD45N4 may be replaced by any of the following products:



#### Drive Products ATV930D45N4

variable speed drive, ATV930, 45kW, 400/480V, with braking unit, IP21

Qty 1

Reason for Substitution: End of life | Substitution date: 01 April 2016



#### Drive Products ATV930D55N4

variable speed drive, ATV930, 55kW, 400/480V, with braking unit, IP21

Qty 1

Reason for Substitution: End of life | Substitution date: 01 April 2016



#### Variable speed drives ATV340D45N4E

variable speed drive - 45kW- 400V - 3 phases - ATV340 Ethernet

Qty 1

Reason for Substitution: End of life | Substitution date: 01 April 2016