SKKD 701



SEMIPACK[®]5

Rectifier Diode Modules


SKKD 701

Features


- Heat transfer through aluminium nitride ceramic insulated metal baseplate
- Precisious metal pressure contacts for high reliability
- UL recognized, file no. E63532


Typical Applications*


- Uncontrolled rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controller
- Field supply for DC motors
- 1) see assembly instructions





Symbol	Conditions	Values	Units
I _{FAV}	sin. 180; T _c = 100 (85) °C	701 (820)	Α
I _{FSM}	T _{vi} = 25 °C; 10 ms	25000	Α
	T_{vi}^{3} = 160 °C; 10 ms	22500	Α
i²t	T _{vi} = 25 °C; 8,3 10 ms	3125000	A²s
	T _{vj} = 160 °C; 8,3 10 ms	2531250	A²s
V _F	T _{vi} = 25 °C; I _F = 2000 A	max. 1,25	V
V _(TO)	T _{vi} = 160 °C	max. 0,7	V
r _T	T _{vj} = 160 °C	max. 0,28	$m\Omega$
I_{RD}	T_{vj} = 160 °C, V_{RD} = V_{RRM}	max. 30	mA
R _{th(j-c)}	cont.; per diode / per module	0,069 / 0,034	K/W
- 0 -/	sin. 180; per diode / per module	0,072 / 0,036	K/W
	rec. 120; per diode / per module	0,077 / 0,038	K/W
$R_{th(c-s)}$	per diode / per module	0,02 / 0,01	K/W
T _{vi} ´		- 40 + 160	°C
T _{stg}		- 40 + 125	°C
V _{isol}	a.c. 50 Hz, r.m.s.; 1 s / 1 min.	3600 / 3000	V~
V _{isol}	a.c. 50 Hz, r.m.s.; 1 s / 1 min. for SKK H4	4800 / 4000	V~
M _s	to heatsink	5 ± 15 % ¹⁾	Nm
Mt	to terminals	12 ± 15 %	Nm
а		5 * 9,81	m/s²
m	approx.	1400	g
Case		A 60b	






















SKKD 701











This is an electrostatic discharge sensitive device (ESDS), international standard IEC 60747-1, chapter IX.

*IMPORTANT INFORMATION AND WARNINGS

The specifications of SEMIKRON products may not be considered as guarantee or assurance of product characteristics ("Beschaffenheitsgarantie"). The specifications of SEMIKRON products describe only the usual characteristics of products to be expected in typical applications, which may still vary depending on the specific application. Therefore, products must be tested for the respective application in advance. Application adjustments may be necessary. The user of SEMIKRON products is responsible for the safety of their applications embedding SEMIKRON products and must take adequate safety measures to prevent the applications from causing a physical injury, fire or other problem if any of SEMIKRON products become faulty. The user is responsible to make sure that the application design is compliant with all applicable laws, regulations, norms and standards. Except as otherwise explicitly approved by SEMIKRON in a written document signed by authorized representatives of SEMIKRON, SEMIKRON products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury. No representation or warranty is given and no liability is assumed with respect to the accuracy, completeness and/or use of any information herein, including without limitation, warranties of non-infringement of intellectual property rights of any third party. SEMIKRON does not assume any liability arising out of the applications or use of any product; neither does it convey any license under its patent rights, copyrights, trade secrets or other intellectual property rights, nor the rights of others. SEMIKRON makes no representation or warranty of non-infringement or alleged non-infringement of intellectual property rights of any third party which may arise from applications. Due to technical requirements our products may contain dangerous substances. For information on the types in question please contact the nearest SEMIKRON sales office. This document supersedes and replaces all information previously supplied and may be superseded by updates. SEMIKRON reserves the right to make changes.