


SK 40 DT



SEMITOP® 3

Controllable Bridge Rectifier

SK 40 DT

Preliminary Data

Features


- Compact design
- One screw mounting
- Heat transfer and insulation through direct copper bonded aluminium oxide ceramic (DBC)
- Glass passivated thyristor chips
- Up to 1600V reverse voltage
- UL recognized, file no. E 63 532

Typical Applications*





- Soft starters
- Light control
- Temperature control
- Motor control

| V_{RSM} V | V_{RRM}, V_{DRM} V | $I_D = 42$ A (full conduction) ($T_s = 80$ °C) |
|----------------|-------------------------|--|
| 900 | 800 | SK 40 DT 08 |
| 1300 | 1200 | SK 40 DT 12 |
| 1700 | 1600 | SK 40 DT 16 |

| Symbol | Conditions | Values | Units |
|------------------|---|---------------|--------------------------------------|
| I_D | $T_s = 80$ °C | 42 | A |
| I_{FSM} | $T_{vj} = 25$ °C; 10 ms $T_{vj} = 125$ °C; 10 ms | 320 280 | A A |
| i^2t | $T_{vj} = 25$ °C; 8,3 ... 10 ms $T_{vj} = 125$ °C; 8,3...10 ms | 510 390 | A ² s A ² s |
| V_T | $T_{vj} = 25$ °C; 75A | max. 2,45 | V |
| $V_{T(TO)}$ | $T_{vj} = 125$ °C; | max. 1,1 | V |
| r_T | $T_{vj} = 125$ °C | max. 20 | mΩ |
| I_{DD}, I_{RD} | $T_{vj} = 125$ °C; $V_{DD} = V_{DRM}; V_{RD} = V_{RRM}$ | max. 8 | mA |
| t_{gd} | $T_{vj} =$ °C; $I_G =$ A; $di_G/dt =$ A/μs | | μs |
| t_{gr} | $V_D = \cdot V_{DRM}$ | | μs |
| $(dv/dt)_{cr}$ | $T_{vj} = 125$ °C | max. 1000 | V/μs |
| $(di/dt)_{cr}$ | $T_{vj} = 125$ °C; $f = 50..60$ Hz | max. 100 | A/μs |
| t_q | $T_{vj} = 125$ °C; typ. | 80 | μs |
| I_H | $T_{vj} = 25$ °C; typ. / max. | 80 / 150 | mA |
| I_L | $T_{vj} = 25$ °C; $R_G = 33$ Ω | 150 / 300 | mA |
| V_{GT} | $T_{vj} = 25$ °C; d.c. | min. 2 | V |
| I_{GT} | $T_{vj} = 25$ °C; d.c. | min. 100 | mA |
| V_{GD} | $T_{vj} = 125$ °C; d.c. | max. 0,25 | V |
| I_{GD} | $T_{vj} = 125$ °C; d.c. | max. 3 | mA |
| $R_{th(j-s)}$ | Per thyristor | 1,7 | K/W |
| T_{solder} | Terminals, 10s | 260 | K/W °C |
| T_{vj} | | -40...+125 | °C |
| T_{stg} | | -40...+125 | °C |
| V_{isol} | a. c. 50 Hz; r.m.s.; 1 s / 1 min. | 3000 (2500) | V |
| M_s | Mounting torque to heatsink | 2,5 | Nm |
| m | weight | 30 | g |
| Case | SEMITOP® 3 | T 15 | |



DT








Fig. 5 Gate trigger characteristics



Case T15 (Suggested hole diameter in the PCB for mounting plastic pins and for solder pins= 2mm)



* The specifications of our components may not be considered as an assurance of component characteristics. Components have to be tested for the respective application. Adjustments may be necessary. The use of SEMIKRON products in life support appliances and systems is subject to prior specification and written approval by SEMIKRON. We therefore strongly recommend prior consultation of our personal.