

accessories circuit breaker 3WL shunt trip DC 30V, 100% ed

Model				
product brand name	SENTRON			
product designation	Accessories			
design of the product	Auxiliary release			
General technical data				
closing apparent power [VA]	15 V·A			
closing active power [W]	15 W			
minimum command time / at Us = 100%	60 ms			
make time / electrical	100 ms			
opening time / of circuit breaker / at Us = 100%	80 ms			
Voltage				
surge voltage resistance	4 kV			
Control current				
control supply voltage (Us) / at DC / rated value	30 V			
Adjustable parameters				
operating range / of the voltage trigger				
• minimum	0.7			
• maximum	1.1			
response value				
• of pick-up voltage / minimum	0.7			
extended operating range / of the voltage trigger / for battery operation				
• minimum	0.7			
• maximum	1.26			
Short circuit				
design of the DIAZED fuse link gG/miniature circuit breaker with tripping characteristic class C 100% / for short-circuit protection / minimum permissible	1 A TDz (slow)/1 A			
Connections				
connectable conductor cross-section				
• minimum	0.5 mm ²			
• maximum	1.5 mm ²			
AWG number / as coded connectable conductor cross section / for auxiliary contacts				
• minimum	20			
• maximum	16			
Environmental conditions				
ambient temperature / during operation				
• minimum	-40 °C			
• maximum	70 °C			
ambient temperature / during storage				
• minimum	-40 °C			
• maximum	80 °C			
General Product Approval	EMC	Declaration of Conformity	Test Certificates	other



[Miscellaneous](#)

[Environmental Con-
firmations](#)

[Manufacturer De-
claration](#)

other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3WL9111-0AD02-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL9111-0AD02-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3WL9111-0AD02-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

