

accessories circuit breaker 3WL 1st trip signalling switch 1 CO; S24

Model				
product brand name	SENTRON			
product designation	1st trip alarm switch			
design of the product	Accessories			
General technical data				
degree of pollution	3			
Voltage				
surge voltage resistance / rated value	4 kV			
Supply voltage				
operating voltage				
<ul style="list-style-type: none"> at AC / at 50 Hz / rated value / maximum at DC / rated value / maximum 	250 V 250 V			
Current				
operational current				
<ul style="list-style-type: none"> at AC-12 / at 230 V / rated value at DC-12 / at 230 V / rated value at DC-12 / at 110 V / rated value at DC-12 / at 24 V / rated value 	8 A 0.2 A 0.4 A 6 A			
Short circuit				
design of the DIAZED fuse link gG / for short-circuit protection / maximum permissible	6 A Dz (quick)			
General Product Approval	EMC	Declaration of Conformity	Test Certificates	other



[Miscellaneous](#)

[Manufacturer Declaration](#)

[Environmental Conformations](#)

other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3WL9111-0AH14-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3WL9111-0AH14-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3WL9111-0AH14-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

