

Infeed terminal 25 mm<sup>2</sup> short for pin busbars



Model	
product brand name	SETRON
product designation	Busbar systems
design of the product	Accessories
operational current / at AC / rated value	80 A
operating voltage / at AC / rated value	690 V
Connections	
tightening torque	
• minimum	1 N·m
• maximum	2 N·m
type of connectable conductor cross-sections / for copper conductor / stranded	6 - 25 mm <sup>2</sup>
Mechanical Design	
height	17.7 mm
width	17 mm
depth	16.8 mm
length	38.2 mm
net weight	12 g
General Product Approval	

[Miscellaneous](#)



### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3768>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3768>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5ST3768](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3768)

Tender specifications

<http://www.siemens.com/specifications>

