



Circuit breaker Universal current 440 V DC 400 V AC 10kA, 2-pole, C, 32A

Model	
product brand name	SENTRON
product designation	Miniature circuit breaker
General technical data	
number of poles	2
number of poles / note	2P
tripping characteristic class	C
mechanical service life (switching cycles) / typical	10 000
overvoltage category	III
degree of pollution	3
Voltage	
insulation voltage	
• at DC / rated value	250 V
• with single-phase operation / at AC / rated value	440 V
• with multi-phase operation / at AC / rated value	440 V
Supply voltage	
type of voltage	AC/DC
supply voltage	
• at AC / rated value	400 V
• at DC / rated value	440 V
operating voltage / at DC / rated value / maximum	500 V
supply voltage frequency / rated value	50/60 Hz
Protection class	
protection class IP	IP20, with connected conductors
Switching capacity	
switching capacity current	
• at DC / acc. to IEC 60947-2 / rated value	15 kA
• acc. to EN 60898 / rated value	10 kA
energy limitation class	3
Dissipation	
power loss [W] / for rated value of the current / at AC / in hot operating state / per pole	2.6 W
suitability for operation	universal current
Product details	
product function / neutral conductor switching	No
product feature / touch protection	Yes
product component	

<ul style="list-style-type: none"> combined terminal top combined terminal bottom 	<p>Yes</p> <p>Yes</p>
product feature <ul style="list-style-type: none"> properties for main switches in accordance with EN 60204-1 halogen-free sealable silicon-free 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes</p>
product extension / installable / supplementary devices	<p>Yes</p>
Short circuit	
breaking capacity short-circuit current (I_{cn}) <ul style="list-style-type: none"> at DC / acc. to EN 60898-2 	<p>10 kA</p>
Connections	
connectable conductor cross-section / solid <ul style="list-style-type: none"> minimum maximum 	<p>0.75 mm²</p> <p>35 mm²</p>
connectable conductor cross-section / stranded <ul style="list-style-type: none"> minimum maximum 	<p>0.75 mm²</p> <p>35 mm²</p>
connectable conductor cross-section / finely stranded / with core end processing <ul style="list-style-type: none"> minimum maximum 	<p>0.75 mm²</p> <p>25 mm²</p>
AWG number / as coded connectable conductor cross section <ul style="list-style-type: none"> minimum maximum 	<p>18</p> <p>4</p>
tightening torque [lbf-in] / with screw-type terminals <ul style="list-style-type: none"> minimum maximum 	<p>22 lbf-in</p> <p>31 lbf-in</p>
tightening torque / with screw-type terminals <ul style="list-style-type: none"> minimum maximum 	<p>2.5 N-m</p> <p>3.5 N-m</p>
position / of power supply cord	<p>AC as required, observe DC polarity</p>
Mechanical Design	
height	90 mm
width	36 mm
depth	76 mm
installation depth	70 mm
number of modular width units	2
fastening method	Quick assembly system
mounting position	any
net weight	323 g
Environmental conditions	
influence of the surrounding temperature	max. 95% to 55°C, max. 55% to 70°C, max. 35% to 75°C
vibration resistance / acc. to IEC 60068-2-6	±1mm at 5 to 25Hz; 50m/s ² at 25 to 150Hz
ambient temperature / during operation <ul style="list-style-type: none"> minimum maximum 	<p>-40 °C</p> <p>70 °C</p>
ambient temperature / during storage <ul style="list-style-type: none"> minimum maximum 	<p>-40 °C</p> <p>75 °C</p>
number of test cycles / for environmental testing / acc. to IEC 60068-2-30	6
Certificates	
reference code <ul style="list-style-type: none"> acc. to DIN EN 61346-2 acc. to IEC 81346-2 	<p>F</p> <p>F</p>



[Miscellaneous](#)



Test Certificates

Railway

[Special Test Certificate](#)

[Special Test Certificate](#)

[Miscellaneous](#)

[Confirmation](#)

[Vibration and Shock](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SY5232-7>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SY5232-7>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SY5232-7

Tender specifications

<http://www.siemens.com/specifications>

