



SHUNT TRIP LEFT 24 V AC 50/60 HZ / 24-30 V DC ACCESSORY FOR 3VA1 and 3VA20 up to 3VA25

Model	
product brand name	SETRON
product designation	Accessories
Product version	Auxiliary release
Accessories	Auxiliary release
General technical data	
Degree of pollution	3
Overvoltage category	III
apparent power consumption / maximum	30 V·A
consumed active power / at DC / maximum	45 W
Voltage	
Tension assignée d'isolement Ui	690 V
surge voltage resistance	4 kV
control supply voltage (Us) / at AC	24 V 50/60 Hz
control supply voltage (Us) / at DC	24 - 30 V
Current	
Mechanical Design	
Height	65.1 mm
Width	25.7 mm
number of slots	3
depth	31.2 mm
net weight	91 g
tightening torque / with screw-type terminals / minimum	0.4 N·m
tightening torque / with screw-type terminals / maximum	0.5 N·m
Connections according IEC	
stripped length	10 mm
AWG number / as coded connectable conductor cross section / for auxiliary contacts	
• minimum	20
• maximum	16
Connections according UL	
stripped length [in]	0.4 in
tightening torque [lbf·in] / with screw-type terminals / minimum	3.5 lbf·in
tightening torque [lbf·in] / with screw-type terminals / maximum	4.4 lbf·in
Certificates	

**General Product Approval**[Miscellaneous](#)

EG-Konf.



EG-Konf.

**Declaration of Conformity**

EG-Konf.





EG-Konf.

**Test Certificates**[Type Test  
Certificates/Test  
Report](#)[Type Test  
Certificates/Test  
Report](#)[Type Test  
Certificates/Test  
Report](#)**Shipping Approval**

LRS

**other**[Manufacturer  
Declaration](#)[Miscellaneous](#)**Further information****Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9988-0BL30>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3VA9988-0BL30>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=3VA9988-0BL30](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9988-0BL30)**Tender specifications**<http://www.siemens.com/specifications>



last modified:

5/6/2020 