

SIPLUS HMI KTP600 Basic Color PN -25...+60°C with conformal coating based on "6AV6647-0AD11-3AX0" "5.7" TFT "display, 256 colors" Ethernet" interface



General information

Product type designation	KTP600 Basic color PN
--------------------------	-----------------------

Display

Design of display	TFT
Screen diagonal	5.7 in
Display width	115.2 mm
Display height	86.4 mm
Number of colors	256

Resolution (pixels)

- | | |
|-------------------------------|-----------|
| • Horizontal image resolution | 320 Pixel |
| • Vertical image resolution | 240 Pixel |

Backlighting

- | | |
|--------------------------------|----------|
| • MTBF backlighting (at 25 °C) | 50 000 h |
| • Backlight dimmable | No |

Control elements

Keyboard fonts

- | | |
|---------------------------|---|
| • Function keys | |
| — Number of function keys | 6 |

— Number of function keys with LEDs	0
• Keys with LED	No
• System keys	No
• Numeric keyboard	Yes; Onscreen keyboard
• alphanumeric keyboard	Yes; Onscreen keyboard
Touch operation	
• Design as touch screen	Yes
Installation type/mounting	
Mounting position	vertical
Rack mounting	No
Wall mounting/direct mounting	No
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	35°
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.35 A
Starting current inrush I ² t	0.5 A ² ·s
Power	
Active power input, typ.	9 W
Processor	
Processor type	RISC 32 bit
Memory	
Flash	Yes
RAM	Yes
Memory available for user data	1 Mbyte
Type of output	
Acoustics	Sound signal
• Buzzer	Yes
• Speaker	No
Time of day	
Clock	
• Hardware clock (real-time)	No
• Software clock	Yes

- retentive
- synchronizable

No
Yes

Interfaces

Number of industrial Ethernet interfaces	1
Number of RS 485 interfaces	0
Number of RS 422 interfaces	0
Number of RS 232 interfaces	0
Number of USB interfaces	0
Number of 20 mA interfaces (TTY)	0
Number of parallel interfaces	0
Number of other interfaces	0
Number of SD card slots	0
With software interfaces	No

Industrial Ethernet

- Industrial Ethernet status LED

2

Protocols

PROFINET	Yes
Supports protocol for PROFINET IO	No
IRT	No
PROFIBUS	No
MPI	No

Protocols (Ethernet)

- TCP/IP
- DHCP
- SNMP
- DCP
- LLDP

Yes
Yes
Yes
Yes
Yes

WEB characteristics

- HTTP
- HTML

No
No

Further protocols

- CAN
- EtherNet/IP
- MODBUS

No
Yes
Yes; Modicon (MODBUS TCP/IP)

Interrupts/diagnostics/status information

Diagnoses

- Diagnostic information readable

No

Degree and class of protection

IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	

• Enclosure Type 4 at the front	Yes
• Enclosure Type 4x at the front	Yes
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	No
Ambient temperature during operation	
• Operation (vertical installation)	
— For vertical installation, min.	-25 °C
— For vertical installation, max.	60 °C
• Operation (max. tilt angle)	
— At maximum tilt angle, min.	-25 °C
— At maximum tilt angle, min.	40 °C
Ambient temperature during storage/transportation	
• min.	-30 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Remark	

— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04

* The supplied plug covers must remain in place over the unused interfaces during operation!

Conformal coating	
<ul style="list-style-type: none"> • Coatings for printed circuit board assemblies acc. to EN 61086 	Yes; Class 2 for high reliability
<ul style="list-style-type: none"> • Protection against fouling acc. to EN 60664-3 	Yes; Type 1 protection
<ul style="list-style-type: none"> • Military testing according to MIL-I-46058C, Amendment 7 	Yes; Discoloration of coating possible during service life
<ul style="list-style-type: none"> • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A 	Yes; Conformal coating, Class A

Operating systems	
proprietary	Yes
pre-installed operating system	
<ul style="list-style-type: none"> • Windows CE 	No

Configuration	
Message indicator	Yes
Alarm system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes

Configuration software	
<ul style="list-style-type: none"> • STEP 7 Basic (TIA Portal) 	Yes; via integrated WinCC Basic (TIA Portal)
<ul style="list-style-type: none"> • STEP 7 Professional (TIA Portal) 	Yes; via integrated WinCC Basic (TIA Portal)
<ul style="list-style-type: none"> • WinCC flexible Compact 	Yes
<ul style="list-style-type: none"> • WinCC flexible Standard 	Yes
<ul style="list-style-type: none"> • WinCC flexible Advanced 	Yes
<ul style="list-style-type: none"> • WinCC Basic (TIA Portal) 	Yes
<ul style="list-style-type: none"> • WinCC Comfort (TIA Portal) 	Yes
<ul style="list-style-type: none"> • WinCC Advanced (TIA Portal) 	Yes
<ul style="list-style-type: none"> • WinCC Professional (TIA Portal) 	Yes

Languages	
Online languages	
<ul style="list-style-type: none"> • Number of online/runtime languages 	5
Project languages	
<ul style="list-style-type: none"> • Languages per project 	32

Functionality under WinCC (TIA Portal)	
Libraries	Yes
Applications/options	none
<ul style="list-style-type: none"> • Web browser 	No

• SIMATIC WinCC Sm@rtServer	No
Task planner	
• time-controlled	No
• task-controlled	Yes
Help system	
• Number of characters per info text	320
Message system	
• Number of alarm classes	32
• Bit messages	Yes
— Number of bit messages	200
• Analog messages	Yes
— Number of analog messages	15
• System messages HMI	Yes
• System messages, other (SIMATIC S7, Sinumerik, Simotion, etc.)	No
• Number of characters per message	80
• Number of process values per message	8
• Message indicator	Yes
• Message buffer	Ring buffer (n x 256 entries), non-retentive
— Number of entries	256
— Circulating buffer	Yes
— retentive	Yes
— maintenance-free	Yes
Recipe management	
• Number of recipes	5
• Data records per recipe	20
• Entries per data record	20
• Size of internal recipe memory	40 kbyte
• Recipe memory expandable	No
Variables	
• Number of variables per device	500
• Number of variables per screen	30
• Limit values	Yes
• Multiplexing	Yes
• Structures	No
• Arrays	Yes
Images	
• Number of configurable images	50
• Permanent window/default	Yes
• Global image	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes

Image objects	
• Number of objects per image	30
• Text fields	Yes
• I/O fields	Yes
• Graphic I/O fields (graphics list)	Yes
• Symbolic I/O fields (text list)	Yes
• Date/time fields	Yes
• Switches	Yes
• Buttons	Yes
• Graphic display	Yes
• Icons	Yes
• Geometric objects	Yes
Complex image objects	
• Number of complex objects per screen	5
• Alarm view	Yes
• Trend view	Yes
• User view	Yes
• Status/control	No
• Sm@rtClient view	No
• Recipe view	Yes
• f(x) trend view	No
• System diagnostics view	No
• Media Player	No
• Bar graphs	Yes
• Sliders	No
• Pointer instruments	No
• Analog/digital clock	No
Lists	
• Number of text lists per project	150
• Number of entries per text list	30
• Number of graphics lists per project	100
• Number of entries per graphics list	30
Archiving	
• Number of archives per device	0
Security	
• Number of user groups	50
• Number of user rights	32
• Number of users	50
• Password export/import	No
• SIMATIC Logon	No
Character sets	

<ul style="list-style-type: none"> • Keyboard fonts <ul style="list-style-type: none"> — US English 	US American (English) Yes
Transfer (upload/download)	
<ul style="list-style-type: none"> • MPI/PROFIBUS DP 	No
<ul style="list-style-type: none"> • USB 	No
<ul style="list-style-type: none"> • Ethernet 	Yes
<ul style="list-style-type: none"> • using external storage medium 	No
Process coupling	
<ul style="list-style-type: none"> • S7-1200 	Yes
<ul style="list-style-type: none"> • S7-1500 	Yes
<ul style="list-style-type: none"> • S7-200 	Yes
<ul style="list-style-type: none"> • S7-300/400 	Yes
<ul style="list-style-type: none"> • LOGO! 	Yes; With restrictions with regard to address area and data types http://support.automation.siemens.com/WW/view/en/56348902
<ul style="list-style-type: none"> • WinAC 	Yes
<ul style="list-style-type: none"> • SINUMERIK 	No
<ul style="list-style-type: none"> • SIMOTION 	No
<ul style="list-style-type: none"> • Allen Bradley (EtherNet/IP) 	Yes
<ul style="list-style-type: none"> • Allen Bradley (DF1) 	No
<ul style="list-style-type: none"> • Mitsubishi (MC TCP/IP) 	Yes
<ul style="list-style-type: none"> • Mitsubishi (FX) 	No
<ul style="list-style-type: none"> • OMRON (FINS TCP) 	No
<ul style="list-style-type: none"> • OMRON (LINK/Multilink) 	No
<ul style="list-style-type: none"> • Modicon (Modbus TCP/IP) 	Yes
<ul style="list-style-type: none"> • Modicon (Modbus) 	No
Service tools/configuration aids	
<ul style="list-style-type: none"> • Backup/Restore manually 	Yes
<ul style="list-style-type: none"> • Backup/Restore automatically 	No
<ul style="list-style-type: none"> • Simulation 	Yes
<ul style="list-style-type: none"> • Device switchover 	Yes
Peripherals/Options	
Printer	No
SIMATIC HMI MM memory card: Multi Media Card	No
SIMATIC HMI SD memory card: Secure Digital memory card	No
USB memory	No
Mechanics/material	
Enclosure material (front)	
<ul style="list-style-type: none"> • Plastic 	Yes
<ul style="list-style-type: none"> • Aluminum 	No
<ul style="list-style-type: none"> • Stainless steel 	No

Dimensions

Width of the housing front	214 mm
Height of housing front	158 mm
Mounting cutout, width	197 mm
Mounting cutout, height	141 mm
Overall depth	44 mm

Weights

Weight without packaging	1.07 kg
Weight incl. packaging	1.32 kg

last modified: 10/09/2020