

SIMATIC HMI KP8 PN Key Panel, 8 short-stroke switches with multi-colored LEDs, PROFINET interfaces 8 configurable DI/DO pins, 24 V DC can be looped through parameterizable as of STEP 7 V5.5



General information

Product type designation KP8 PN

Control elements

With parameterizable keys Yes

Keyboard fonts

- Membrane keyboard
 - user-definable label membrane keys Yes
- Function keys
 - Number of function keys 8
- Short-stroke keys
 - Number of short-stroke keys 8

Expansions for operator control of the process

- DP direct LEDs (LEDs as S7 output I/O) 8; Adjustable brightness
- Number of color modes for LED 5; red, green, blue, yellow, white
- Direct keys (keys as S7 input I/O) 8

Installation type/mounting

Mounting type Mounting clip

Mounting position vertical

Rack mounting	No
Front mounting	Yes; Compatible with Extension Units dimensions
Rail mounting	No
Wall mounting/direct mounting	No
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	30°; To the front/rear
Number of slots for command devices and signaling units	0

Supply voltage

Type of supply voltage	DC
Rated value (DC)	24 V; 24 V can be looped through connector, interrupted when pulled
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V

Input current

Current consumption (rated value)	0.3 A
-----------------------------------	-------

Type of output

LED colors	
• red	Yes
• yellow	Yes
• green	Yes
• white	Yes
• blue	Yes

Digital inputs

Number of digital inputs	8; Total inputs and outputs max. 8 and 1x SIL 2 or 2x SIL 3
--------------------------	---

Input voltage

• Rated value (DC)	24 V
--------------------	------

Digital outputs

Number of digital outputs	8; Max. 8 inputs and outputs (total)
---------------------------	--------------------------------------

Short-circuit protection	Yes
--------------------------	-----

Switching capacity of the outputs

• with resistive load, max.	100 mA
-----------------------------	--------

Output voltage

• Rated value (DC)	24 V; Non-isolated
--------------------	--------------------

Total current of the outputs

• Current per channel, max.	100 mA
• Current per group, max.	800 mA

Interfaces

Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
--	--

Number of PROFINET interfaces	2; Incl. switch
Industrial Ethernet	
• Industrial Ethernet status LED	2; Per port
• Number of ports of the integrated switch	2; Per port
Protocols	
PROFINET	Yes; also 3rd party PLC
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
IRT	Yes
PROFIsafe	No
PROFIBUS	No
MPI	No
AS-Interface	No
EIB/KNX	No
Protocols (Ethernet)	
• TCP/IP	No
Redundancy mode	
Media redundancy	
— MRP	Yes
Further protocols	
• AS-Interface Safety at Work	No
• CAN	No
• Data-Highway	No
• DeviceNet	No
• DeviceNet Safety	No
• EtherNet/IP	No
• Foundation Fieldbus	No
• INTERBUS	No
• INTERBUS-Safety	No
• Local Operating Network	No
• MODBUS	No
• SafetyBUS p	No
• SERCOS	No
• SUCOnet	No
• other bus systems	No
Test commissioning functions	
Illuminant test	Yes; During switch on
Key and signal lamp test	Yes; automatically when switching on
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes; Group 1, measured at a distance of 10 m

- Limit class B, for use in residential areas

No

Degree and class of protection

IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
<ul style="list-style-type: none"> • Enclosure Type 4 at the front 	No
<ul style="list-style-type: none"> • Enclosure Type 4x at the front 	Yes; Incl. NEMA12

Standards, approvals, certificates

CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Suitable for safety functions	Yes

Use in hazardous areas

<ul style="list-style-type: none"> • ATEX Zone 2 	Yes
<ul style="list-style-type: none"> • ATEX Zone 22 	Yes
<ul style="list-style-type: none"> • cULus Class I Zone 1 	No
<ul style="list-style-type: none"> • cULus Class I Zone 2, Division 2 	Yes
<ul style="list-style-type: none"> • FM Class I Division 2 	Yes

Marine approval

<ul style="list-style-type: none"> • Germanischer Lloyd (GL) 	No
<ul style="list-style-type: none"> • American Bureau of Shipping (ABS) 	No
<ul style="list-style-type: none"> • Bureau Veritas (BV) 	No
<ul style="list-style-type: none"> • Det Norske Veritas (DNV) 	No
<ul style="list-style-type: none"> • Lloyds Register of Shipping (LRS) 	No
<ul style="list-style-type: none"> • Nippon Kaiji Kyokai (Class NK) 	No
<ul style="list-style-type: none"> • Polski Rejestr Statkow (PRS) 	No

Ambient conditions

Ambient temperature during operation	
<ul style="list-style-type: none"> • min. 	0 °C
<ul style="list-style-type: none"> • max. 	55 °C
<ul style="list-style-type: none"> • Operation (vertical installation) 	
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — For vertical installation, min. 	0 °C
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — For vertical installation, max. 	55 °C
<ul style="list-style-type: none"> • Operation (max. tilt angle) 	
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — At maximum tilt angle, min. 	0 °C
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — At maximum tilt angle, min. 	45 °C
<ul style="list-style-type: none"> • Operation (vertical installation, portrait format) 	
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — For vertical installation, min. 	0 °C
<ul style="list-style-type: none"> <ul style="list-style-type: none"> — For vertical installation, max. 	55 °C

<ul style="list-style-type: none"> • Operation (max. tilt angle, portrait format) <ul style="list-style-type: none"> — At maximum tilt angle, min. 0 °C — At maximum tilt angle, min. 45 °C 	
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> • min. -20 °C • max. 60 °C 	
Relative humidity	
<ul style="list-style-type: none"> • Operation, max. 95 %; no condensation 	

Configuration

Configuration software

- | | |
|---|--|
| <ul style="list-style-type: none"> • STEP 7 Basic (TIA Portal) • STEP 7 Professional (TIA Portal) | <ul style="list-style-type: none"> Yes Yes |
|---|--|

Functionality under WinCC (TIA Portal)

Process coupling

- | | |
|---|---|
| <ul style="list-style-type: none"> • S7-1200 • S7-1500 • S7-200 • S7-300/400 • LOGO! • WinAC • SINUMERIK • SIMOTION • Allen Bradley (EtherNet/IP) • Allen Bradley (DF1) • Mitsubishi (MC TCP/IP) • Mitsubishi (FX) • OMRON (FINS TCP) • OMRON (LINK/Multilink) • Modicon (Modbus TCP/IP) • Modicon (Modbus) | <ul style="list-style-type: none"> Yes; with ET 200pro CPU and ET 200S CPU Yes No Yes; with F-CPU: STEP 7 V11 SP1 (or higher) and Safety V11 (or higher) or SIMATIC STEP 7 Basic V11 (or higher) No Yes No No No No No No No No No No No |
|---|---|

Mechanics/material

Enclosure material (front)

- | | |
|--|---|
| <ul style="list-style-type: none"> • Plastic • Aluminum • Stainless steel | <ul style="list-style-type: none"> Yes No No |
|--|---|

Service life

- | | |
|---|--|
| <ul style="list-style-type: none"> • Short-stroke keys (in switching cycles) • LEDs (ON period) | <ul style="list-style-type: none"> 1 500 000 100 % |
|---|--|

Dimensions

Width of the housing front	98 mm
Height of housing front	155 mm
Mounting cutout, width	68 mm; Max. thickness of mounting plate 2 - 6 mm
Mounting cutout, height	129 mm
Overall depth	49 mm; Incl. angled SIMATIC Ethernet connector

Weights

Weight without packaging	280 g
--------------------------	-------

last modified: 10/13/2020