



General information	
Product function	
• Location identifier	Yes
FH technology	
Safety evaluation through direct wiring	
• Reconnection without emergency stop circuit interruption	Yes
• Monitoring the STOP button	Yes
Supply voltage	
Type of supply voltage	24 V DC
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.5 A
Power	
Active power input, typ.	12 W
Interfaces	

Interfaces/bus type	1x RS 232, 1x RS 422, 1x RS 485 (max. 12 Mbit/s)
Number of RS 485 interfaces	1
Number of RS 422 interfaces	1
Number of RS 232 interfaces	1
Number of 20 mA interfaces (TTY)	0
Connection point identification	Yes

### Standards, approvals, certificates

CE mark	Yes
CSA approval	No
UL approval	No
cULus	Yes
RCM (formerly C-TICK)	Yes
EAC (formerly Gost-R)	No
Marine approval	No

### Use in hazardous areas

<ul style="list-style-type: none"> <li>• ATEX Zone 2</li> </ul>	No
<ul style="list-style-type: none"> <li>• ATEX Zone 22</li> </ul>	No
<ul style="list-style-type: none"> <li>• FM Class I Division 2</li> </ul>	No

### Ambient conditions

#### Ambient temperature during operation

<ul style="list-style-type: none"> <li>• Operation (vertical installation)</li> </ul>	0 to +50 °C
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— For vertical installation, min.</li> </ul> </li> </ul>	0 °C
<ul style="list-style-type: none"> <li> <ul style="list-style-type: none"> <li>— For vertical installation, max.</li> </ul> </li> </ul>	50 °C

#### Ambient temperature during storage/transportation

<ul style="list-style-type: none"> <li>• min.</li> </ul>	-20 °C
<ul style="list-style-type: none"> <li>• max.</li> </ul>	70 °C

#### Relative humidity

<ul style="list-style-type: none"> <li>• Operation, max.</li> </ul>	85 %
---	------

### Dimensions

Width	160 mm
Height	120 mm
Depth	70 mm

### Weights

Weight (without packaging)	0.4 kg
----------------------------	--------

### Other

free hotline	Yes
--------------	-----

#### Usable in the following products

<ul style="list-style-type: none"> <li>• Product 1</li> </ul>	6AV6645-0A*
<ul style="list-style-type: none"> <li>• Product 2</li> </ul>	6AV6645-0C*
<ul style="list-style-type: none"> <li>• Product 3</li> </ul>	<a href="#">6AV6645-0BE02-0AX0</a>

last modified:

10/13/2020