

circuit breaker VL250H high breaking capacity I_{cu}=70kA, 415V AC 3-pole, non-auto. air circ. br. Electronic Trip Unit magnetic I_n=250A, rated current I_I=3500A, short-circuit protection without auxiliary release without auxiliary/alarm switch

Model	
type of the driving mechanism / motor drive	No
design of the overcurrent release	M
General technical data	
number of poles	3
size of the circuit-breaker	3VL3
mechanical service life (switching cycles) / typical	20 000
electrical endurance (switching cycles) / typical	10 000
utilization category	A
performance class for circuit breaker	N
reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	Q
operating frequency / maximum	120 1/s
Voltage	
Rated operational voltage U _e / max.	690 V
insulation voltage	
• rated value	800 V
• at AC / rated value	800 V
surge voltage resistance / rated value	8 kV
operating voltage	
• rated value / maximum	690 V
• for main current circuit / at AC / at 50 Hz / maximum	690 V
• for main current circuit / at AC / at 60 Hz / maximum	690 V
• for main current circuit / at DC / maximum	500 V
Protection class	
protection class IP	IP20
protection function of the overcurrent release	I
Current	
operational current	
• at 40 °C / rated value	250 A
• at 45 °C / rated value	250 A
• at 50 °C / rated value	250 A
• at 55 °C / rated value	232.5 A
• at 60 °C / rated value	232.5 A
• at 65 °C / rated value	215 A
• at 70 °C / rated value	215 A
continuous current / rated value	250 A
derating temperature / for the rated value of the continuous current	50 °C
adjustable current response value current	
• of instantaneous short-circuit trip unit / initial value	3 500 A
• of instantaneous short-circuit trip unit / full-scale value	3 500 A
Main circuit	
operating frequency	
• 1 / rated value	50 Hz
• 2 / rated value	60 Hz

Auxiliary circuit	
number of CO contacts / for auxiliary contacts	0
number of NC contacts / for auxiliary contacts	0
number of NO contacts / for auxiliary contacts	0
Suitability	
suitability for use	non-automatic circuit-breakers
Product details	
product component	
<ul style="list-style-type: none"> • trip indicator 	No
<ul style="list-style-type: none"> • auxiliary switch 	No
<ul style="list-style-type: none"> • voltage trigger 	No
<ul style="list-style-type: none"> • undervoltage release 	No
<ul style="list-style-type: none"> • undervoltage release with leading contact 	No
product extension / optional / motor drive	Yes
Product function	
product function	
<ul style="list-style-type: none"> • of thermal overload trip unit 	without
<ul style="list-style-type: none"> • grounding protection 	No
<ul style="list-style-type: none"> • for neutral conductors / short-circuit and overload proof 	No
<ul style="list-style-type: none"> • overload protection 	No
Short circuit	
breaking capacity operating short-circuit current (Ics)	
<ul style="list-style-type: none"> • at 240 V / rated value 	75 kA
<ul style="list-style-type: none"> • at 415 V / rated value 	70 kA
<ul style="list-style-type: none"> • at 500 V / rated value 	30 kA
<ul style="list-style-type: none"> • at 690 V / rated value 	6 kA
breaking capacity maximum short-circuit current (Icu)	
<ul style="list-style-type: none"> • at 240 V / rated value 	100 kA
<ul style="list-style-type: none"> • at 415 V / rated value 	70 kA
<ul style="list-style-type: none"> • at 440 V / rated value 	50 kA
<ul style="list-style-type: none"> • at 480 V / acc. to NEMA / rated value 	50 kA
<ul style="list-style-type: none"> • at 500 V / rated value 	40 kA
<ul style="list-style-type: none"> • at 600 V / acc. to NEMA / rated value 	12 kA
<ul style="list-style-type: none"> • at 690 V / rated value 	12 kA
Connections	
arrangement of electrical connectors / for main current circuit	front side
type of connectable conductor cross-sections / for main contacts	
<ul style="list-style-type: none"> • with flexible busbar 	17 x 10 mm
<ul style="list-style-type: none"> • solid 	25 ... 185 mm ²
<ul style="list-style-type: none"> • finely stranded / with core end processing 	25 ... 120 mm ²
<ul style="list-style-type: none"> • stranded 	25 ... 185 mm ²
type of connectable conductor cross-sections / for auxiliary contacts	
<ul style="list-style-type: none"> • solid 	0.75 ... 1.5 mm ²
<ul style="list-style-type: none"> • finely stranded / with core end processing 	0,75 ... 1.0 mm ²
type of electrical connection / for main current circuit	screw-type terminals
Mechanical Design	
height	185.5 mm
width	104.5 mm
depth	106.5 mm
fastening method	fixed mounting
Environmental conditions	
ambient temperature / during operation	
<ul style="list-style-type: none"> • minimum 	0 °C
<ul style="list-style-type: none"> • maximum 	70 °C

ambient temperature / during storage	
<ul style="list-style-type: none"> • minimum • maximum 	-40 °C 80 °C
Certificates	
certificate of suitability	IEC, high switching capacity (H)
reference code	
<ul style="list-style-type: none"> • acc. to DIN EN 61346-2 	Q
General Product Approval	EMC



[Miscellaneous](#)

[TSE](#)

[KC](#)



Declaration of Conformity	Test Certificates	Marine / Shipping
----------------------------------	--------------------------	--------------------------



[Special Test Certificate](#)



Marine / Shipping	other
--------------------------	--------------



[Confirmation](#)

[Environmental Confirmations](#)

[Manufacturer Declaration](#)

other

[Miscellaneous](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=3VL3725-2DE36-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3VL3725-2DE36-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mfb=3VL3725-2DE36-0AA0

CAx-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>

