

SIPLUS S7-1500 DQ 8x24 V DC/2A -40...+70°C with conformal coating based on 6ES7522-1BF00-0AB0 . Digital "output module ""DQ 8x24 V DC/2A" "HF;"" ""8 channels in groups of" "8;"" ""8 A per group;"" ""diagnostics; substitute value"



Figure similar

General information	
Product type designation	DQ 8x24VDC/2A HF
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> <li>Isochronous mode</li> <li>Fast startup</li> </ul>	Yes; I&M0 to I&M3 No Yes; 500 ms
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption, max.	40 mA; 20 mA per group, no output is activated.
Power	
Power available from the backplane bus	0.9 W
Power loss	
Power loss, typ.	5.6 W

Digital outputs	
Type of digital output	Transistor
Number of digital outputs	8; > +60 °C Number of simultaneously controllable outputs max. 8x 0.5 A, max. total current per group 2 A
Digital outputs, parameterizable	Yes
Short-circuit protection	Yes
<ul style="list-style-type: none"> <li>• Response threshold, typ.</li> </ul>	3 A
Limitation of inductive shutdown voltage to	-17 V
Switching capacity of the outputs	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	2 A
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	10 W
Load resistance range	
<ul style="list-style-type: none"> <li>• lower limit</li> </ul>	12 Ω
<ul style="list-style-type: none"> <li>• upper limit</li> </ul>	4 kΩ
Output voltage	
<ul style="list-style-type: none"> <li>• for signal "1", min.</li> </ul>	L+ (-0.8 V)
Output current	
<ul style="list-style-type: none"> <li>• for signal "1" rated value</li> </ul>	2 A
<ul style="list-style-type: none"> <li>• for signal "1" permissible range, max.</li> </ul>	2.4 A
<ul style="list-style-type: none"> <li>• for signal "0" residual current, max.</li> </ul>	0.5 mA
Output delay with resistive load	
<ul style="list-style-type: none"> <li>• "0" to "1", max.</li> </ul>	100 μs
<ul style="list-style-type: none"> <li>• "1" to "0", max.</li> </ul>	500 μs
Parallel switching of two outputs	
<ul style="list-style-type: none"> <li>• for logic links</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for uprating</li> </ul>	No
<ul style="list-style-type: none"> <li>• for redundant control of a load</li> </ul>	Yes
Switching frequency	
<ul style="list-style-type: none"> <li>• with resistive load, max.</li> </ul>	100 Hz
<ul style="list-style-type: none"> <li>• with inductive load, max.</li> </ul>	0.5 Hz; According to IEC 60947-5-1, DC-13
<ul style="list-style-type: none"> <li>• on lamp load, max.</li> </ul>	10 Hz
Total current of the outputs	
<ul style="list-style-type: none"> <li>• Current per channel, max.</li> </ul>	2 A; note derating data in the manual
<ul style="list-style-type: none"> <li>• Current per group, max.</li> </ul>	8 A; note derating data in the manual
<ul style="list-style-type: none"> <li>• Current per module, max.</li> </ul>	16 A; note derating data in the manual
Cable length	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	1 000 m
<ul style="list-style-type: none"> <li>• unshielded, max.</li> </ul>	600 m
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Substitute values connectable	Yes

Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	No
• Short-circuit	Yes
• Fuse blown	No
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED
• for channel diagnostics	Yes; red LED
• for module diagnostics	Yes; red LED
Potential separation	
Potential separation channels	
• between the channels	Yes
• between the channels, in groups of	4
• between the channels and backplane bus	Yes
Permissible potential difference	
between different circuits	75 V DC/60 V AC
Isolation	
Isolation tested with	707 V DC (type test)
Standards, approvals, certificates	
Suitable for safety functions	No
Ambient conditions	
Ambient temperature during operation	
• horizontal installation, min.	-40 °C; = Tmin (incl. condensation/frost)
• horizontal installation, max.	70 °C; = Tmax; > +60 °C Number of simultaneously controllable outputs max. 8x 0.5 A, max. total current per group 2 A
• vertical installation, min.	-40 °C; = Tmin
• vertical installation, max.	40 °C; = Tmax
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	5 000 m
• Ambient air temperature-barometric pressure-altitude	Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
• With condensation, tested in accordance with IEC 60068-2-38, max.	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)

Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)
— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
<ul style="list-style-type: none"> <li>• Coatings for printed circuit board assemblies acc. to EN 61086</li> <li>• Protection against fouling acc. to EN 60664-3</li> <li>• Military testing according to MIL-I-46058C, Amendment 7</li> <li>• Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A</li> </ul>	<p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	240 g

last modified:

10/13/2020