

SIPLUS S7-1500 DQ 16X24VDC/0.5A -40 ... +70°C MIT conformal coating based on 6ES7522-1BH01-0AB0 . 16 CHANNELS IN GROUPS OF 8, 4 A "PER GROUP; SINGLE-CHANNEL" "DIAGNOSIS; SUBSTITUTE VALUE"

| General information | |
|--|---|
| Product type designation | DQ 16x24VDC/0.5A HF |
| Firmware version | |
| <ul style="list-style-type: none"> FW update possible | Yes |
| Product function | |
| <ul style="list-style-type: none"> I&M data | Yes; I&M0 to I&M3 |
| <ul style="list-style-type: none"> Isochronous mode | Yes |
| <ul style="list-style-type: none"> Prioritized startup | Yes |
| Operating mode | |
| <ul style="list-style-type: none"> DQ | Yes |
| <ul style="list-style-type: none"> DQ with energy-saving function | No |
| <ul style="list-style-type: none"> PWM | No |
| <ul style="list-style-type: none"> Oversampling | No |
| <ul style="list-style-type: none"> MSO | Yes |
| Supply voltage | |
| Rated value (DC) | 24 V |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes; through internal protection with 7 A per group |
| Input current | |
| Current consumption, max. | 30 mA |
| Output voltage | |
| Rated value (DC) | 24 V |
| Power | |
| Power available from the backplane bus | 1.1 W |
| Power loss | |
| Power loss, typ. | 2 W |
| Digital outputs | |
| Type of digital output | Transistor |
| Number of digital outputs | 16 |
| Current-sourcing | Yes |
| Digital outputs, parameterizable | Yes |

| | |
|--|---|
| Short-circuit protection | Yes; Clocked electronically |
| <ul style="list-style-type: none"> • Response threshold, typ. | 1 A |
| Limitation of inductive shutdown voltage to | L+ (-53 V) |
| Controlling a digital input | Yes |
| Switching capacity of the outputs | |
| <ul style="list-style-type: none"> • with resistive load, max. | 0.5 A |
| <ul style="list-style-type: none"> • on lamp load, max. | 5 W |
| Load resistance range | |
| <ul style="list-style-type: none"> • lower limit | 48 Ω |
| <ul style="list-style-type: none"> • upper limit | 12 kΩ |
| Output voltage | |
| <ul style="list-style-type: none"> • for signal "1", min. | L+ (-0.8 V) |
| Output current | |
| <ul style="list-style-type: none"> • for signal "1" rated value | 0.5 A |
| <ul style="list-style-type: none"> • for signal "1" permissible range, max. | 0.5 A |
| <ul style="list-style-type: none"> • for signal "0" residual current, max. | 0.5 mA |
| Output delay with resistive load | |
| <ul style="list-style-type: none"> • "0" to "1", max. | 100 μs |
| <ul style="list-style-type: none"> • "1" to "0", max. | 500 μs |
| Parallel switching of two outputs | |
| <ul style="list-style-type: none"> • for logic links | Yes |
| <ul style="list-style-type: none"> • for uprating | No |
| <ul style="list-style-type: none"> • for redundant control of a load | Yes |
| Switching frequency | |
| <ul style="list-style-type: none"> • with resistive load, max. | 100 Hz |
| <ul style="list-style-type: none"> • with inductive load, max. | 0.5 Hz; According to IEC 60947-5-1, DC-13 |
| <ul style="list-style-type: none"> • on lamp load, max. | 10 Hz |
| Total current of the outputs | |
| <ul style="list-style-type: none"> • Current per channel, max. | 0.5 A; see additional description in the manual |
| <ul style="list-style-type: none"> • Current per group, max. | 4 A; see additional description in the manual |
| <ul style="list-style-type: none"> • Current per module, max. | 8 A; see additional description in the manual |
| Cable length | |
| <ul style="list-style-type: none"> • shielded, max. | 1 000 m |
| <ul style="list-style-type: none"> • unshielded, max. | 600 m |
| Isochronous mode | |
| Execution and activation time (TCO), min. | 70 μs |
| Bus cycle time (TDP), min. | 250 μs |
| Interrupts/diagnostics/status information | |
| Diagnostics function | Yes |
| Substitute values connectable | Yes |
| Alarms | |

| | |
|---|---|
| • Diagnostic alarm | Yes |
| Diagnoses | |
| • Monitoring the supply voltage | Yes |
| • Wire-break | Yes |
| • Short-circuit | Yes |
| • Group error | Yes |
| Diagnostics indication LED | |
| • RUN LED | Yes; green LED |
| • ERROR LED | Yes; red LED |
| • Monitoring of the supply voltage (PWR-LED) | Yes; green LED |
| • Channel status display | Yes; green LED |
| • for channel diagnostics | Yes; red LED |
| • for module diagnostics | Yes; red LED |
| Potential separation | |
| Potential separation channels | |
| • between the channels | No |
| • between the channels, in groups of | 8 |
| • between the channels and backplane bus | Yes |
| Isolation | |
| Isolation tested with | 707 V DC (type test) |
| Standards, approvals, certificates | |
| Suitable for safety functions | No |
| Ambient conditions | |
| Ambient temperature during operation | |
| • horizontal installation, min. | -40 °C; = Tmin (incl. condensation/frost) |
| • horizontal installation, max. | 70 °C; = Tmax; see Derating BasedOn (e.g. manual), additionally Tmax > 60 °C max. aggregate current 2 A per group |
| Altitude during operation relating to sea level | |
| • Installation altitude above sea level, max. | 5 000 m |
| • Ambient air temperature-barometric pressure-altitude | Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax -20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m) |
| Relative humidity | |
| • With condensation, tested in accordance with IEC 60068-2-38, max. | 100 %; RH incl. condensation / frost (no commissioning in bedewed state), horizontal installation |
| Resistance | |
| Coolants and lubricants | |
| — Resistant to commercially available coolants and lubricants | Yes; Incl. diesel and oil droplets in the air |
| Use in stationary industrial systems | |

| | |
|---|---|
| — to biologically active substances according to EN 60721-3-3 | Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request |
| — to chemically active substances according to EN 60721-3-3 | Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-3 | Yes; Class 3S4 incl. sand, dust, * |
| Use on ships/at sea | |
| — to biologically active substances according to EN 60721-3-6 | Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request |
| — to chemically active substances according to EN 60721-3-6 | Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); * |
| — to mechanically active substances according to EN 60721-3-6 | Yes; Class 6S3 incl. sand, dust; * |
| Usage in industrial process technology | |
| — Against chemically active substances acc. to EN 60654-4 | Yes; Class 3 (excluding trichlorethylene) |
| — Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04 | Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil) |
| Remark | |
| — Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04 | * The supplied plug covers must remain in place over the unused interfaces during operation! |
| Conformal coating | |
| • Coatings for printed circuit board assemblies acc. to EN 61086 | Yes; Class 2 for high reliability |
| • Protection against fouling acc. to EN 60664-3 | Yes; Type 1 protection |
| • Military testing according to MIL-I-46058C, Amendment 7 | Yes; Discoloration of coating possible during service life |
| • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A | Yes; Conformal coating, Class A |
| Dimensions | |
| Width | 35 mm |
| Height | 147 mm |
| Depth | 129 mm |
| Weights | |
| Weight, approx. | 230 g |
| last modified: | 10/13/2020 |