

SIPLUS S7-1500 TM Count 2x24V -40...+70°C with conformal coating based on 6ES7550-1AA00-0AB0 . Counter module, 2 channels for 24 V incremental or encoder 3 DI, 2 DQ per channel



Figure similar

General information	
Product type designation	TM Count 2x24V
Product function	
<ul style="list-style-type: none"> • I&M data 	Yes
<ul style="list-style-type: none"> • Isochronous mode 	Yes
Installation type/mounting	
Rail mounting	Yes; S7-1500 mounting rail
Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> • Rated value (DC) 	24 V
<ul style="list-style-type: none"> • permissible range, lower limit (DC) 	19.2 V
<ul style="list-style-type: none"> • permissible range, upper limit (DC) 	28.8 V
<ul style="list-style-type: none"> • Reverse polarity protection 	Yes
Input current	
Current consumption, max.	75 mA; without load

Encoder supply	
Number of outputs	1; A common 24V encoder supply for both channels
24 V encoder supply	
<ul style="list-style-type: none"> • 24 V • Short-circuit protection • Output current, max. 	Yes; L+ (-0.8 V) Yes 1 A; Total current of all encoders / channels; > +60 °C max. total current 0.5 A
Power	
Power available from the backplane bus	1.3 W
Power loss	
Power loss, typ.	4 W
Address area	
Address space per module	
<ul style="list-style-type: none"> • Inputs • Outputs 	16 byte; Per channel 12 byte; per channel; 4 bytes for Motion Control
Digital inputs	
Number of digital inputs	6; 3 per channel
Digital inputs, parameterizable	Yes
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Digital input functions, parameterizable	
<ul style="list-style-type: none"> • Gate start/stop • Capture • Synchronization • Freely usable digital input 	Yes Yes Yes Yes
Input voltage	
<ul style="list-style-type: none"> • Rated value (DC) • for signal "0" • for signal "1" • permissible voltage at input, min. • permissible voltage at input, max. 	24 V -30 to +5 V +11 to +30V -30 V 30 V
Input current	
<ul style="list-style-type: none"> • for signal "1", typ. 	2.5 mA
Input delay (for rated value of input voltage)	
for standard inputs	
<ul style="list-style-type: none"> — parameterizable — at "0" to "1", min. — at "1" to "0", min. 	Yes; none / 0.05 / 0.1 / 0.4 / 0.8 / 1.6 / 3.2 / 12.8 / 20 ms 6 µs; for parameterization "none" 6 µs; for parameterization "none"
for technological functions	
<ul style="list-style-type: none"> — parameterizable 	Yes
Cable length	

- shielded, max. 1 000 m
- unshielded, max. 600 m

Digital outputs

Type of digital output	Transistor
Number of digital outputs	4; 2 per channel
Digital outputs, parameterizable	Yes
Short-circuit protection	
<ul style="list-style-type: none"> • Response threshold, typ. 	1 A
Limitation of inductive shutdown voltage to	L+ (-33 V)
Controlling a digital input	Yes
Digital output functions, parameterizable	
<ul style="list-style-type: none"> • Switching tripped by comparison values 	Yes
<ul style="list-style-type: none"> • Freely usable digital output 	Yes
Switching capacity of the outputs	
<ul style="list-style-type: none"> • with resistive load, max. 	0.5 A; Per digital output
<ul style="list-style-type: none"> • on lamp load, max. 	5 W
Load resistance range	
<ul style="list-style-type: none"> • lower limit 	48 Ω
<ul style="list-style-type: none"> • upper limit 	12 kΩ
Output voltage	
<ul style="list-style-type: none"> • for signal "1", min. 	23.2 V; L+ (-0.8 V)
Output current	
<ul style="list-style-type: none"> • for signal "1" rated value 	0.5 A; Per digital output
<ul style="list-style-type: none"> • for signal "1" permissible range, max. 	0.6 A; Per digital output
<ul style="list-style-type: none"> • for signal "1" minimum load current 	2 mA
<ul style="list-style-type: none"> • for signal "0" residual current, max. 	0.5 mA
Output delay with resistive load	
<ul style="list-style-type: none"> • "0" to "1", max. 	50 μs
<ul style="list-style-type: none"> • "1" to "0", max. 	50 μs
Switching frequency	
<ul style="list-style-type: none"> • with resistive load, max. 	10 kHz
<ul style="list-style-type: none"> • with inductive load, max. 	0.5 Hz; Acc. to IEC 60947-5-1, DC-13; observe derating curve
<ul style="list-style-type: none"> • on lamp load, max. 	10 Hz
Total current of the outputs	
<ul style="list-style-type: none"> • Current per module, max. 	2 A; > +60 °C max. total current of outputs 1 A
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m

Encoder

Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	Yes

— permissible quiescent current (2-wire sensor), max.	1.5 mA
Encoder signals, incremental encoder (asymmetrical)	
• Input voltage	24 V
• Input frequency, max.	200 kHz
• Counting frequency, max.	800 kHz; with quadruple evaluation
• Cable length, shielded, max.	600 m; depending on input frequency, encoder and cable quality; max. 50 m at 200 kHz
• Signal filter, parameterizable	Yes
• Incremental encoder with A/B tracks, 90° phase offset	Yes
• Incremental encoder with A/B tracks, 90° phase offset and zero track	Yes
• Pulse encoder	Yes
• Pulse encoder with direction	Yes
• Pulse encoder with one impulse signal per count direction	Yes
Encoder signal 24 V	
— permissible voltage at input, min.	-30 V
— permissible voltage at input, max.	30 V
Interface types	
• Source/sink input	Yes
• Input characteristic curve in accordance with IEC 61131, type 3	Yes
Isochronous mode	
Filtering and processing time (TCI), min.	130 µs
Bus cycle time (TDP), min.	250 µs
Interrupts/diagnostics/status information	
Alarms	
• Diagnostic alarm	Yes
• Hardware interrupt	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire-break	Yes
• Short-circuit	Yes
• A/B transition error at incremental encoder	Yes
Diagnostics indication LED	
• RUN LED	Yes; green LED
• ERROR LED	Yes; red LED
• MAINT LED	Yes; Yellow LED
• Monitoring of the supply voltage (PWR-LED)	Yes; green LED
• Channel status display	Yes; green LED

- for channel diagnostics Yes; red LED
- Status indicator forward counting (green) Yes
- Status indicator backward counting (green) Yes

Integrated Functions

Number of counters	2
Counting frequency (counter) max.	800 kHz; with quadruple evaluation
Counting functions	
• Can be used with TO High_Speed_Counter	Yes
• Continuous counting	Yes
• Counter response parameterizable	Yes
• Hardware gate via digital input	Yes
• Software gate	Yes
• Event-controlled stop	Yes
• Synchronization via digital input	Yes
• Counting range, parameterizable	Yes
Comparator	
— Number of comparators	2; Per channel
— Direction dependency	Yes
— Can be changed from user program	Yes
Position detection	
• Suitable for S7-1500 Motion Control	Yes
Measuring functions	
• Measuring time, parameterizable	Yes
• Dynamic measurement period adjustment	Yes
• Number of thresholds, parameterizable	2
Measuring range	
— Frequency measurement, min.	0.04 Hz
— Frequency measurement, max.	800 kHz
— Cycle duration measurement, min.	1.25 μ s
— Cycle duration measurement, max.	25 s
Accuracy	
— Frequency measurement	100 ppm; depending on measuring interval and signal evaluation
— Cycle duration measurement	100 ppm; depending on measuring interval and signal evaluation
— Velocity measurement	100 ppm; depending on measuring interval and signal evaluation
Potential separation	
Potential separation channels	
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	No
Isolation	

Isolation tested with	707 V DC (type test)
Ambient conditions	
Ambient temperature during operation	
<ul style="list-style-type: none"> horizontal installation, min. horizontal installation, max. 	-40 °C; = Tmin (incl. condensation/frost); start-up @ -25 °C 70 °C; = Tmax; note derating for inductive loads; > +60 °C total current of the encoder supply max. 0.5 A, total current of the outputs max. 1 A
<ul style="list-style-type: none"> vertical installation, min. vertical installation, max. 	-40 °C; = Tmin; Startup @ -25 °C 40 °C; Please note derating for inductive loads
Ambient temperature during storage/transportation	
<ul style="list-style-type: none"> min. max. 	-40 °C 70 °C
Altitude during operation relating to sea level	
<ul style="list-style-type: none"> Installation altitude above sea level, max. Ambient air temperature-barometric pressure-altitude 	5 000 m Tmin ... Tmax at 1 140 hPa ... 795 hPa (-1 000 m ... +2 000 m) // Tmin ... (Tmax - 10 K) at 795 hPa ... 658 hPa (+2 000 m ... +3 500 m) // Tmin ... (Tmax - 20 K) at 658 hPa ... 540 hPa (+3 500 m ... +5 000 m)
Relative humidity	
<ul style="list-style-type: none"> With condensation, tested in accordance with IEC 60068-2-38, max. 	100 %; RH incl. condensation/frost (no commissioning under condensation conditions)
Resistance	
Coolants and lubricants	
— Resistant to commercially available coolants and lubricants	Yes; Incl. diesel and oil droplets in the air
Use in stationary industrial systems	
— to biologically active substances according to EN 60721-3-3	Yes; Class 3B2 mold, fungus and dry rot spores (with the exception of fauna); Class 3B3 on request
— to chemically active substances according to EN 60721-3-3	Yes; Class 3C4 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust, *
Use on ships/at sea	
— to biologically active substances according to EN 60721-3-6	Yes; Class 6B2 mold and fungal spores (excluding fauna); Class 6B3 on request
— to chemically active substances according to EN 60721-3-6	Yes; Class 6C3 (RH < 75 %) incl. salt spray acc. to EN 60068-2-52 (severity degree 3); *
— to mechanically active substances according to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust; *
Usage in industrial process technology	
— Against chemically active substances acc. to EN 60654-4	Yes; Class 3 (excluding trichlorethylene)

— Environmental conditions for process, measuring and control systems acc. to ANSI/ISA-71.04	Yes; Level GX group A/B (excluding trichlorethylene; harmful gas concentrations up to the limits of EN 60721-3-3 class 3C4 permissible); level LC3 (salt spray) and level LB3 (oil)
Remark	
— Note regarding classification of environmental conditions acc. to EN 60721, EN 60654-4 and ANSI/ISA-71.04	* The supplied plug covers must remain in place over the unused interfaces during operation!
Conformal coating	
<ul style="list-style-type: none"> • Coatings for printed circuit board assemblies acc. to EN 61086 • Protection against fouling acc. to EN 60664-3 • Military testing according to MIL-I-46058C, Amendment 7 • Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies according to IPC-CC-830A 	<p>Yes; Class 2 for high reliability</p> <p>Yes; Type 1 protection</p> <p>Yes; Discoloration of coating possible during service life</p> <p>Yes; Conformal coating, Class A</p>
Decentralized operation	
to SIMATIC S7-1500	Yes
to standard PROFINET controller	Yes
Dimensions	
Width	35 mm
Height	147 mm
Depth	129 mm
Weights	
Weight, approx.	250 g
last modified:	10/13/2020