

SIMATIC S7-1500, Front connector Screw-type connection system, 40-pole for 35 mm wide modules incl. 4 potential bridges, and cable ties



Figure similar

General information	
Product type designation	Front connector
Connection method	
Connection I/O signals	
<ul style="list-style-type: none"> <li>• Connection method</li> <li>• Number of lines per connection</li> </ul>	<p>Screw terminals</p> <p>1; or combination of 2 conductors of up to 1.5 mm<sup>2</sup> (total) in a shared ferrule</p>
Conductor cross-section in mm <sup>2</sup>	
— Connectable cable cross-sections for massive cables, min.	0.25 mm <sup>2</sup>
— Connectable cable cross-sections for massive cables, min.	1.5 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables without end sleeve, min.	0.25 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables without end sleeve, max.	1.5 mm <sup>2</sup>
— Connectable cable cross-sections for flexible cables with end sleeve, min.	0.25 mm <sup>2</sup>

— Connectable cable cross-sections for flexible cables with end sleeve, max.	1.5 mm <sup>2</sup>
<b>Conductor cross-section acc. to AWG</b>	
— Connectable cable cross-sections for massive cables, min.	24
— Connectable cable cross-sections for massive cables, min.	16
— Connectable cable cross-sections for flexible cables without end sleeve, min.	24
— Connectable cable cross-sections for flexible cables without end sleeve, max.	16
— Connectable cable cross-sections for flexible cables with end sleeve, min.	24
— Connectable cable cross-sections for flexible cables with end sleeve, max.	16
<b>Wire end processing</b>	
— Stripped length of cables, min.	10 mm
— Stripped length of cables, max.	11 mm
— End sleeve acc. to DIN 46228 without plastic sleeve	Form A, 10 mm and 12 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Form E, 10 mm and 12 mm long
<b>Mounting</b>	
— Tool	Screwdriver, conical design, 3 mm to 3.5 mm
— Tightening torque, min.	0.4 N·m
— Tightening torque, max.	0.7 N·m
<b>Dimensions</b>	
Width	29.8 mm
Height	130.5 mm
Depth	46 mm
<b>Weights</b>	
Weight, approx.	123 g
<b>last modified:</b>	10/09/2020