

SIPLUS DC-USV-MODUL 24V/40A  
 SIPLUS PS DC UPS module 24 V/40 A -25...+70°C with conformal coating based on 6EP1931-2FC21 . Uninterruptible Power supply without interface Input: 24 V DC/43 A Output: 24 V DC/40 A



Figure similar

Input	
supply voltage at DC rated value	24 V
voltage curve at input	DC
input voltage range	22 ... 29 V DC
adjustable response value voltage for buffer connection preset	22.5 V
adjustable response value voltage for buffer connection	22 ... 25.5 V; Adjustable in 0.5 V increments
input current at rated input voltage 24 V rated value	40 A; + approx. 2.6 A with empty battery
Mains buffering	
type of energy storage	with batteries
design of the mains power cut bridging-connection	Dependent on connected battery and load current, see selection table battery module and mains buffering times as well as the relevant important information notes!
charging current	1 A, 2 A
adjustable charging current maximum note	factory setting approx. 2 A
Output	

output voltage	
<ul style="list-style-type: none"> <li>• in normal operation at DC rated value</li> <li>• in buffering mode at DC rated value</li> </ul>	24 V 24 V
formula for output voltage	$V_{in} - \text{approx. } 0.5 \text{ V}$
ON-delay time typical	1 s
voltage increase time of the output voltage typical	360 ms
output voltage in buffering mode at DC	19 ... 28.5 V
output current	
<ul style="list-style-type: none"> <li>• rated value</li> <li>• in normal operation</li> <li>• in buffering mode</li> </ul>	40 A 0 ... 40 A 0 ... 40 A
peak current	42 A
supplied active power typical	960 W

### Efficiency

efficiency in percent	
<ul style="list-style-type: none"> <li>• at rated output current for rated value of the output current typical</li> <li>• in case of accumulator operation typical</li> </ul>	97.2 % 96.9 %
power loss [W]	
<ul style="list-style-type: none"> <li>• at rated output current for rated value of the output current typical</li> <li>• in case of accumulator operation typical</li> </ul>	28.6 W 33.6 W

### Protection and monitoring

product function	
<ul style="list-style-type: none"> <li>• reverse polarity protection against energy storage unit polarity reversal</li> <li>• reverse polarity protection against input voltage polarity reversal</li> </ul>	Yes Yes

### Signaling

display version	
<ul style="list-style-type: none"> <li>• for normal operation</li> </ul>	Normal operation: LED green (OK), floating changeover contact "Bat/OK" to setting "OK" ("OK" means: Voltage of the supplying power supply unit is greater than cut-in threshold set at the DC UPS module); Lack of buffer standby: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Battery replacement required: LED red (alarm) flashing with approx. 0.25 Hz, floating changeover contact "Alarm/Bat" switching with approx. 0.25 Hz; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed; Permissible contact current capacity: DC 60 V/1 A or AC 30 V /1 A

- in buffering mode

Buffered mode: LED yellow (Bat), floating changeover contact "OK/Bat" to setting "Bat"; Prewarning battery voltage < 20.4 VDC: LED red (alarm), floating changeover contact "Alarm/Bat" to setting "Alarm"; Energy storage > 85%: LED green (Bat > 85%), floating NO contact "Bat > 85" closed

Interface	
product component PC interface	No
design of the interface	without

Safety	
galvanic isolation between entrance and outlet	No
operating resource protection class	Class III
certificate of suitability	
<ul style="list-style-type: none"> <li>• CE marking</li> </ul>	Yes
protection class IP	IP20

EMC	
standard	
<ul style="list-style-type: none"> <li>• for emitted interference</li> </ul>	EN 55022 Class B
<ul style="list-style-type: none"> <li>• for interference immunity</li> </ul>	EN 61000-6-2

environmental conditions	
ambient temperature in horizontal mounting position during operation	-25 ... +70; with natural convection
ambient temperature during storage and transport	-40 ... +85
installation altitude at height above sea level maximum	6 000 m
ambient condition relating to ambient temperature - air pressure - installation altitude	In case of operation at altitudes of 2000 - 6000 m above sea level: Output power derating of -7.5 %/1000 m or reduction of the ambient temperature by 5 K/1000 m
relative humidity with condensation acc. to IEC 60068-2-38 maximum	100 %; RH incl. condensation/frost (no commissioning if condensation is present), horizontal installation
chemical resistance to commercially available cooling lubricants	Yes; incl. diesel and oil droplets in the air
resistance to biologically active substances conformity acc. to EN 60721-3-3	Yes; Class 3B2 mold, fungal, sponge spores (except fauna); class 3B3 upon request
resistance to chemically active substances conformity acc. to EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust
resistance to biologically active substances conformity acc. to EN 60721-3-6	Yes; Class 6B2 mold, fungal, sponge spores (except fauna)
resistance to chemically active substances conformity acc. to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity acc. to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust

coating for equipped printed circuit board acc. to EN 61086	Yes; Class 2 for high availability
type of coating protection against pollution according to EN 60664-3	Yes; Type 1 protection
type of test of the coating acc. to MIL-I-46058C	Yes; Discoloration of the coating during service life possible
product conformity of the coating Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal Coating, Class A

## Mechanics

type of electrical connection	screw-type terminals
<ul style="list-style-type: none"> <li>• at input</li> <li>• at output</li> <li>• for battery module</li> <li>• for control circuit and status message</li> </ul>	24 V DC: 2 screw terminals for 0.33 ... 10 mm <sup>2</sup> /22 ... 7 AWG 24 V DC: 2 screw terminals for 0.33 ... 10 mm <sup>2</sup> /22 ... 7 AWG 24 V DC: 2 screw terminals for 0.33 ... 10 mm <sup>2</sup> /22 ... 7 AWG 10 screw terminals for 0.5 ... 2.5 mm <sup>2</sup> /20 ... 13 AWG
width of the enclosure	102 mm
height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing	
<ul style="list-style-type: none"> <li>• top</li> <li>• bottom</li> <li>• left</li> <li>• right</li> </ul>	50 mm 50 mm 0 mm 0 mm
net weight	1.1 kg
product feature of the enclosure housing for side-by-side mounting	Yes
mounting type	Snaps onto DIN rail EN 60715 35x7.5/15
electrical accessories	Battery module
MTBF at 40 °C	522 739 h
reference code acc. to DIN EN 81346-2	T
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)