

SIPPLUS PSE202U REDUNDANZMODUL
 SIPLUS PS E202U redundancy module for medial exposure with conformal coating based on 6EP1961-3BA21 . Input/output: 24 V DC/40 A suitable for decoupling two SITOP power supplies with max. 20 A output current each



Figure similar

Input	
Input	DC voltage
supply voltage	
• at DC	24 ... 24 V
input voltage	
• at DC	24 ... 28.8 V
Output	
Output	Controlled, isolated DC voltage
Rated voltage Vout DC	24 V
• Output voltage	Vin - approx. 0.5 V
product function output voltage adjustable	No
Status display	Green LED for "both Input voltages > switching threshold"; red LED: for "at least one input voltage < switching threshold"
Signaling	Isolated relay contact (changeover contacts, rating 8 A/240 V AC, 24 V DC): Signals OK if both input voltages > switching threshold, setting range of threshold 20 ... 25 V
Rated current value Iout rated	40 A

Current range	40 A
• Note	max. aggregate current 40 A; +60 ... +70 °C: derating 3%/K
Efficiency	
Efficiency at Vout rated, Iout rated, approx.	96.6 %
Power loss at Vout rated, Iout rated, approx.	34 W
power loss [W] during no-load operation maximum	1.5 W
Safety	
galvanic isolation	yes, SELV acc. to EN 60950-1 (relay contact)
Protection class	Class III
Degree of protection (EN 60529)	IP20
Approvals	
CE mark	Yes
EMC	
Emitted interference	EN 55022 Class B
Noise immunity	EN 61000-6-2
environmental conditions	
ambient temperature in horizontal mounting position during operation	0 ... 60; with natural convection
ambient temperature during storage and transport	-40 ... +85
installation altitude at height above sea level maximum	6 000 m
ambient condition relating to ambient temperature - air pressure - installation altitude	In case of operation at altitudes of 2000 - 6000 m above sea level: Output power derating of -7.5 %/1000 m or reduction of the ambient temperature by 5 K/1000 m
relative humidity with condensation acc. to IEC 60068-2-38 maximum	100 %; RH incl. condensation/frost (no commissioning if condensation is present), horizontal installation
chemical resistance to commercially available cooling lubricants	Yes; incl. diesel and oil droplets in the air
resistance to biologically active substances conformity acc. to EN 60721-3-3	Yes; Class 3B2 mold, fungal, sponge spores (except fauna); class 3B3 upon request
resistance to chemically active substances conformity acc. to EN 60721-3-3	Yes; Class 3C4 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity acc. to EN 60721-3-3	Yes; Class 3S4 incl. sand, dust
resistance to biologically active substances conformity acc. to EN 60721-3-6	Yes; Class 6B2 mold, fungal, sponge spores (except fauna)
resistance to chemically active substances conformity acc. to EN 60721-3-6	Yes; Class 6C3 (RH < 75%) incl. salt spray acc. to EN 60068-2-52 (severity level 3)
resistance to mechanically active substances conformity acc. to EN 60721-3-6	Yes; Class 6S3 incl. sand, dust
coating for equipped printed circuit board acc. to EN 61086	Yes; Class 2 for high availability

type of coating protection against pollution according to EN 60664-3	Yes; Type 1 protection
type of test of the coating acc. to MIL-I-46058C	Yes; Discoloration of the coating during service life possible
product conformity of the coating Qualification and Performance of Electrical Insulating Compound for Printed Board Assemblies acc. to IPC-CC-830A	Yes; Conformal Coating, Class A

Mechanics

Connection technology	screw-type terminals
Connections	
<ul style="list-style-type: none"> • Supply input 	Input, output and ground: 1 screw terminal each for 0.33 ... 10 mm ² single-core/finely stranded
<ul style="list-style-type: none"> • Auxiliary 	Relay contact: 3 screw terminals for 0.5 ... 2.5 mm ² single-core/finely stranded
width of the enclosure	70 mm
height of the enclosure	125 mm
depth of the enclosure	120 mm
required spacing	
<ul style="list-style-type: none"> • top 	50 mm
<ul style="list-style-type: none"> • bottom 	50 mm
<ul style="list-style-type: none"> • left 	0 mm
<ul style="list-style-type: none"> • right 	0 mm
Weight, approx.	0.5 kg
product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	6 471 654 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)