

SITOP PSU100D/1AC/24VDC/12.5A

PSU100D 24 V/12.5 A Stabilized power supply input: 100-240 V AC
output: DC 24 V/12,5 A



Input	
Input	1-phase AC
Rated voltage value V_{in} rated	100 ... 240 V
Voltage range AC	85 ... 264 V
Wide-range input	Yes
Mains buffering	at $V_{in} = 115/230$ V
Mains buffering at I_{out} rated, min.	15 ms; at $V_{in} = 115/230$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
• at rated input voltage 100 V	4 A
• at rated input voltage 240 V	2 A
Switch-on current limiting (+25 °C), max.	60 A
I^2t , max.	1.1 A ² ·s
Built-in incoming fuse	internal
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C or from 16 A characteristic B
Output	

Output	Controlled, isolated DC voltage
Rated voltage Vout DC	24 V
Total tolerance, static ±	2 %
Static mains compensation, approx.	0.5 %
Static load balancing, approx.	0.5 %
Residual ripple peak-peak, max.	100 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	100 mV
Adjustment range	22 ... 28 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
Signaling	-
On/off behavior	Overshoot of Vout < 2 %
Startup delay, max.	1 s
voltage increase time of the output voltage maximum	30 ms
Rated current value Iout rated	12.5 A
Current range	0 ... 12.5 A
• Note	+50 ... +70 °C: Derating 2.5%/K
supplied active power typical	300 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency	
Efficiency at Vout rated, Iout rated, approx.	86 %
Power loss at Vout rated, Iout rated, approx.	48 W

Closed-loop control	
Dynamic mains compensation (Vin rated ±15 %), max.	0.5 %
Dynamic load smoothing (Iout: 50/100/50 %), Uout ± typ.	5 %

Protection and monitoring	
Output overvoltage protection	< 35 V
Current limitation, typ.	15 A
property of the output short-circuit proof	Yes
Short-circuit protection	Electronic shutdown, automatic restart
enduring short circuit current RMS value	
• typical	15 A
Overload/short-circuit indicator	-

Safety	
Primary/secondary isolation	Yes
galvanic isolation	Safety extra low output voltage Vout according to EN 60950-1
Protection class	Class I

leakage current	
<ul style="list-style-type: none"> • maximum • typical 	<p>3.5 mA</p> <p>1 mA</p>
Degree of protection (EN 60529)	IP20

Approvals

CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cURus (UL 60950-1, CSA C22.2 No. 60950-1), File E151273
Explosion protection	-
certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
Marine approval	-

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

environmental conditions

ambient temperature	
<ul style="list-style-type: none"> • during operation — Note • during transport • during storage 	<p>-10 ... +70 °C</p> <p>with forced convection (ventilator)</p> <p>-40 ... +85 °C</p> <p>-40 ... +85 °C</p>

Mechanics

Connection technology	screw-type terminals
Connections	
<ul style="list-style-type: none"> • Supply input • Output • Auxiliary 	<p>L, N, PE: 1 screw terminal each for 0.5 ... 1.3 mm² single-core/finely stranded</p> <p>+, -: 2 screw terminals each for 0.5 ... 1.3 mm²</p> <p>-</p>
width of the enclosure	105 mm
height of the enclosure	199 mm
depth of the enclosure	41 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	<p>20 mm</p> <p>0 mm</p> <p>20 mm</p> <p>20 mm</p>
Weight, approx.	0.81 kg
Installation	Wall mounting

