

SITOP PSU100L/1AC/24VDC/20A
 SITOP PSU100L 24 V/20 A Stabilized power supply input: 100-240 V
 AC output: 24 V DC/20 A



Input	
Input	1-phase AC or DC
Rated voltage value V_{in} rated	100 ... 240 V
supply voltage	
• at DC	100 ... 240 V
input voltage	
• 1 at AC	85 ... 264 V
• at DC	88 ... 370 V
Wide-range input	Yes
Mains buffering	at $V_{in} = 93/187$ V
Mains buffering at I_{out} rated, min.	20 ms; at $V_{in} = 93/187$ V
Rated line frequency 1	50 Hz
Rated line frequency 2	60 Hz
Rated line range	47 ... 63 Hz
input current	
• at rated input voltage 120 V	5.55 A
• at rated input voltage 230 V	2.35 A
Switch-on current limiting (+25 °C), max.	45 A
duration of inrush current limiting at 25 °C	

• typical	15 ms
I ² t, max.	3.3 A ² ·s
Built-in incoming fuse	T 10 A/250 V (not accessible)
Protection in the mains power input (IEC 898)	Recommended miniature circuit breaker: from 10 A characteristic C

Output

Output	Controlled, isolated DC voltage
Rated voltage V _{out} DC	24 V
Total tolerance, static ±	3 %
Static mains compensation, approx.	0.1 %
Static load balancing, approx.	1 %
Residual ripple peak-peak, max.	150 mV
Residual ripple peak-peak, typ.	50 mV
Spikes peak-peak, max. (bandwidth: 20 MHz)	240 mV
Spikes peak-peak, typ. (bandwidth: 20 MHz)	100 mV
Adjustment range	22.8 ... 26.4 V
product function output voltage adjustable	Yes
Output voltage setting	via potentiometer
Status display	Green LED for 24 V OK
On/off behavior	No overshoot of V _{out} (soft start)
Startup delay, max.	1.5 s
Voltage rise, typ.	20 ms
Rated current value I _{out} rated	20 A
Current range	0 ... 20 A
• Note	+45 ... +70 °C: Derating 2.5%/K
supplied active power typical	480 W
Parallel switching for enhanced performance	Yes
Numbers of parallel switchable units for enhanced performance	2

Efficiency

Efficiency at V _{out} rated, I _{out} rated, approx.	92 %
Power loss at V _{out} rated, I _{out} rated, approx.	45 W

Closed-loop control

Dynamic mains compensation (V _{in} rated ±15 %), max.	0.5 %
Dynamic load smoothing (I _{out} : 10/90/10 %), U _{out} ± typ.	3 %
Load step setting time 10 to 90%, typ.	0.7 ms
Load step setting time 90 to 10%, typ.	6 ms

Protection and monitoring

Output overvoltage protection	< 33 V
Current limitation, typ.	24 A

property of the output short-circuit proof	Yes
Short-circuit protection	Constant current characteristic
enduring short circuit current RMS value	
• typical	24 A
Overload/short-circuit indicator	-

Safety

Primary/secondary isolation	Yes
galvanic isolation	Safety extra-low output voltage U_{out} acc. to EN 60950-1 and EN 50178
Protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.8 mA
Degree of protection (EN 60529)	IP20

Approvals

CE mark	Yes
UL/cUL (CSA) approval	cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259
Explosion protection	-
certificate of suitability NEC Class 2	No
FM approval	-
CB approval	Yes
Marine approval	-

EMC

Emitted interference	EN 55022 Class B
Supply harmonics limitation	EN 61000-3-2
Noise immunity	EN 61000-6-2

environmental conditions

ambient temperature	
• during operation	-25 ... +70 °C
— Note	with natural convection
• during transport	-40 ... +85 °C
• during storage	-40 ... +85 °C
Humidity class according to EN 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics

Connection technology	screw-type terminals
Connections	
• Supply input	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
• Output	+, -: 2 screw terminals each for 0.5 ... 2.5 mm ²
• Auxiliary	-
width of the enclosure	110 mm

height of the enclosure	125 mm
depth of the enclosure	125 mm
required spacing	
• top	50 mm
• bottom	50 mm
• left	0 mm
• right	0 mm
Weight, approx.	1.8 kg
product feature of the enclosure housing for side-by-side mounting	Yes
Installation	Snaps onto DIN rail EN 60715 35x7.5/15
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)