

SITOP BUF8600 300MS/40A
 SITOP BUF8600 300ms Buffer module for PSU8600 Buffer capacity
 300 ms/40 A with electrolytic capacitors maintenance-free



Mains buffering	
type of energy storage	electrolytic capacitors
design of the mains power cut bridging-connection	Backup time with 40 A load current: 300 ms
buffering time for rated value of the output current in the event of power failure	300 ms
Output	
output current	
<ul style="list-style-type: none"> rated value 	40 A
Signaling	
display version	3-color LED for operating state module
<ul style="list-style-type: none"> for normal operation in buffering mode 	LED green for "buffer standby exist" LED yellow for "buffered mode"
Interface	
design of the interface	Ethernet/PROFINET via power supply unit PSU8600
Safety	
operating resource protection class	Class III
certificate of suitability	

<ul style="list-style-type: none"> • CE marking • as approval for USA • relating to ATEX • C-Tick 	<p>Yes</p> <p>cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)</p> <p>IECEX nA IIC T5 Gc; ATEX (EX) II 3G Ex nA IIC T5 Gc; cCSAus (CSA C22.2 No. 213, ANSI/ISA-12.12.01) Class I, Div. 2, Group ABCD, T5</p> <p>No</p>
type of certification CB-certificate	Yes
shipbuilding approval	ABS, DNV GL
protection class IP	IP20

EMC

standard	
<ul style="list-style-type: none"> • for emitted interference • for interference immunity 	<p>EN 55022 Class B</p> <p>EN 61000-6-2</p>

environmental conditions

ambient temperature	
<ul style="list-style-type: none"> • during operation • during transport • during storage 	<p>-25 ... +60 °C; with natural convection</p> <p>-40 ... +70 °C</p> <p>-40 ... +70 °C</p>
environmental category acc. to IEC 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics

type of electrical connection	-
<ul style="list-style-type: none"> • at input • at output • for control circuit and status message 	-
type of connection to system components	Via integrated connector
width of the enclosure	125 mm
height of the enclosure	125 mm
depth of the enclosure	150 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	<p>50 mm</p> <p>50 mm</p> <p>0 mm</p> <p>0 mm</p>
net weight	2.26 kg
product feature of the enclosure housing for side-by-side mounting	Yes
mounting type	Snaps onto DIN rail EN 60715 35x15
mechanical accessories	Device identification label 20 mm × 7 mm, TI-grey 3RT2900-1SB20
MTBF at 40 °C	4 505 531 h
reference code acc. to DIN EN 81346-2	T

