

SITOP SEL1400 SELEKTIVITY MODUL 4\* 10A  
 SITOP SEL1400 10 A Selectivity module 4-channel with limiting characteristic  
 Input: 24 V DC/40 A Output: 24 V DC/4x 10 A  
 Threshold value adjustable 2-10 A With monitoring interface



Input	
type of the power supply network	Controlled DC voltage
supply voltage / at DC / rated value	24 V
input voltage / at DC	20.4 ... 30 V
overvoltage overload capability	35 V
input current / at rated input voltage 24 V / rated value	40 A
Output	
voltage curve / at output	controlled DC voltage
formula for output voltage	$V_{in} - \text{approx. } 0.2 \text{ V}$
relative overall tolerance / of the voltage / note	In accordance with the supplying input voltage
number of outputs	4
output current / up to 60 °C / per output / rated value	10 A
adjustable pick-up value current / of the current-dependent overload release	2 ... 10 A
type of response value setting	via potentiometer
product feature	
<ul style="list-style-type: none"> <li>parallel switching of outputs</li> </ul>	Yes
<ul style="list-style-type: none"> <li>bridging of equipments</li> </ul>	No

type of outputs connection	Connection of all outputs after ramp-up of the supply voltage > 20 V; delay time of 25 ms, 200 ms, 500 ms or "load-optimized" can be set via DIP switch for sequential connection
----------------------------	---

### Efficiency

efficiency in percent	98 %
power loss [W] / at rated output current / for rated value of the output current / typical	10 W

### Switch-off characteristic per output

switching characteristic	<ul style="list-style-type: none"> <li>• of the excess current</li> <li>• of the current limitation</li> <li>• of the immediate switch-off</li> </ul>
design of the reset device/resetting mechanism	via sensor per output
remote reset function	Non-electrically isolated 24 V input (signal level "high" at > 15 V)

### Protection and monitoring

fuse protection type / at input	15 A per output (not accessible)
display version / for normal operation	Three-color LED per output: green LED for "Output switched through"; yellow LED for "Output switched off manually"; red LED for "Output switched off due to overcurrent"
design of the switching contact / for signaling function	Floating status signal output (pulse/pause signal that can be evaluated via SIMATIC function block)

### Safety

galvanic isolation / between input and output at switch-off	No
standard / for safety	according to EN 60950-1 and EN 50178
operating resource protection class	Class III
protection class IP	IP20

### Approvals

certificate of suitability	Yes
<ul style="list-style-type: none"> <li>• CE marking</li> <li>• UL approval</li> <li>• CSA-approval</li> <li>• ATEX</li> </ul>	<ul style="list-style-type: none"> <li>Yes; UL-Recognized (UL 2367) File E328600; cULus-Listed (UL 508, CSA C22.2 No. 107.1) File E197259</li> <li>Yes; CSA 22.2 60950-1</li> <li>Yes; IECEx Ex ec IIC T4 Gc; ATEX (EX) II 3G Ex ec IIC T4 Gc; cCSAus Class I, Div. 2, Group ABCD, T4</li> </ul>
certificate of suitability	Yes
<ul style="list-style-type: none"> <li>• IECEx</li> </ul>	Yes

### EMC

standard	
<ul style="list-style-type: none"> <li>• for emitted interference</li> <li>• for interference immunity</li> </ul>	<ul style="list-style-type: none"> <li>EN 61000-6-3</li> <li>EN 61000-6-2</li> </ul>

environmental conditions	
ambient temperature	
<ul style="list-style-type: none"> <li>during operation</li> <li>during transport</li> <li>during storage</li> </ul>	-25 ... +70 °C; with natural convection -40 ... +85 °C -40 ... +85 °C
environmental category / acc. to IEC 60721	Climate class 3K3, 5 ... 95% no condensation

Mechanics	
type of electrical connection	Push-in
<ul style="list-style-type: none"> <li>at input</li> <li>at output</li> <li>for signaling contact</li> <li>for auxiliary contacts</li> </ul>	24V1, 24V2: push-in for 0.5 ... 16 mm <sup>2</sup> ; 0V1, 0V2: push-in for 0.5 ... 4 mm <sup>2</sup> 1 - 4: push-in for 0.5 ... 4 mm <sup>2</sup> 13, 14: push-in for 0.2 ... 1.5 mm <sup>2</sup> RST: push-in for 0.2 ... 1.5 mm <sup>2</sup>
width / of the enclosure	45 mm
height / of the enclosure	135 mm
depth / of the enclosure	125 mm
installation width	45 mm
mounting height	225 mm
required spacing	
<ul style="list-style-type: none"> <li>top</li> <li>bottom</li> <li>left</li> <li>right</li> </ul>	45 mm 45 mm 0 mm 0 mm
net weight	0.3 kg
mounting type	Snaps onto DIN rail EN 60715 35x7.5/15
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)